

# Low Cost 15" j1900 complete touch screen pos system

(Model No.: POS8829T)

## Features:

- 1 Good-looking design is suitable for many POS field
- 1 Low power-consumption solution guarantees its stable quality and safety
- 1 LED/LCD customer display optional
- 1 MSR optional
- 1 Wifi optional

## Applications:

- 1 Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- 1 Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- 1 Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- 1 Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

## Specifications:

|                      |   |
|----------------------|---|
| Model                | POS8829T  |
| Optional Color       | Black   |
| Optional Peripherals | ISO Track1/2/3 Magnetic Stripe Reader; LCD Customer display; LED8; WIFI |
| Main Board           | Intel Chipset   |
| CPU                  | 1037U dual core 1.8G  |
| Chipset              | 1037U + ICH8 Chipset  |
| Memory Support       | DDRIII 1066/1333*1 2GB(up to 4GB)                                       |
| Hard Driver          | SATA 2.5 320GB or 500GB or SSD32GB                                      |
| LCD panel Size       | 15 inch TFT LCD   |
| Brightness           | 350cd/m <sup>2</sup>  |
| Resolution           | 1024*768(max)   |
| Touch Screen         | 5 wire resistive touch screen   |
| View Angle           | Horizon: 150; Vertical: 140   |

|                           |  |
|---------------------------|--|
| I/O port                  | 1* power button  |
|                           | PS2 mouse*1; PS2 keyboard*1                                |
|                           | Serial*3 DB9 male  |
|                           | Parallel * 1, DB25 Parallel port                           |
|                           | VGA(15Pin D-sub)*1   |
|                           | LAN: RJ-45*1    HDMI * 1    RJ*11 for cash drawer optional |
|                           | USB(2.0) * 6   |
|                           | Audio out*12*Internal Speaker(option), MIC IN*1            |
| Operating temperature     | 0 to 40 degree centigrade                                  |
| Storage temperature       | -20 to 60 degree centigrade                                |
| Power Consumption         | 35W(max)   |
| Compliance                | FCC Class A/CE Mark/LVD/CCC                                |
| Packing dimension/ Weight | 440*270*425mm / 8 KGS                                      |
| Operating System          | Windows XP Professional Embedded (WEPOS, Linux compatible) |
| Power adapter             | 110-240V/50-60HZ AC power Input, DC12/5A output            |