

80MM Thermal Printer with Auto Cutter

(Model No.: OCPP-80Y)

Features:

1. Desktop or wall-mounted type for option.
2. Supports Multi 1D Barcodes
3. 160mm/s Printing speed
4. supports 256kb nv logo storage and 2m big buffer memory.

Technical parameters

| | |
|----------------------------|---|
| Printing Method: | Direct Thermal |
| Printing speed : | 160 mm |
| Roll width : | 5±0.5mm |
| Print characters: | φ80mm |
| Paper Thickness: | 0.06-0.08mm |
| Column Capacity: | 576dots/line 512 Dots/line |
| Line 's pacing : | 3.75mm □ Adjustable by commands □ |
| Print command: | Compatible with the Esc/pos command |
| Interface Type: | USB |
| C Utters Life: | 1million Monitors |
| P Rint Head Life: | 50000 km |
| Input Buffer : | 2048Kbytes |
| NV Flash: | 256Kbytes |
| Power adaptor : | ac110v/240v □ 50/60Hz |
| Power supply : | DC 24V/2.5A |
| Cash Drawer Supply: | DC 24v/1a |
| Work's : | Temperature (0 ~ 40) °C ~ Humidity (10 ~ 80%) □ No N Condense □ |
| Work's : | Temperature (0-45) Degree Centigrade, Humidity (10-80%) No N Condense |
| Storage's : | Temperature (-10 ~ 60 °C) ; H Umidity (10 ~ 80%) |
| Character size : | Ank □ Fonta: 1.5*3 0MM/FONTB □ 1.1*2.1mm |
| Barcode: | Upc-a/upc-e/ja □ EAN13 □ /jan8 □ Ean8/code39/itf /code93/code128 |
| Characters: | PC347 □ Standard Europe □□ Katakana □ PC850 □ Multilingual □□ PC860 □ Portuguese □□ PC863 □ Canadian-french □□ PC865 □ Nordic □□ West Europe □ Greek □ Hebrew □ East Europe □ Iran □ WPC1252 □ PC866 □ Cyrillic#2 □□ PC852 □ Latin2 □□ PC858 □ Iranii □ Latvian □ Arabic □ PT151 □ 1251 □ |
| Physical characteristics □ | Weight : 1.25Kg |