

Numeric Display Pole Stand Adjustable Point Of Sale Display

Features:

LED POS Customer Pole Display Customer Display
8 characters LED display;
Pole height is adjustable;
360 degree rotation angel;
Compatible with "ESC / POS" standard common instruction set, no need driver, plug and use

Specifications:

Communication	
Interface:	RS232 communication, USB power supply (DC optional)
Baud rate:	2400/9600BPS
Brightness:	1500cd
Handshake signal	No
Electrical	DC5V (from host computer USB interface)
Display:	LED Bright yellow-green digital display
Display characters:	8 Numbers (0~9)
Display area:	160mm x30.8mm
Font size:	13MM*7.6MM
MTBF:	25,000 hours
Physical	
Panel dimensions:	224(L)X88(W)mm
Support dimensions:	Height: 400---442mm Base: 185(L) x95(w) x25(H) mm
Pitching move angle:	8°~120°
Color	White or Black
Weight:	520g (without base);850g (with base);1100g (including packing)
Packing Size	255(L) x 210(W) x 96(H) mm
Environment	
Operating Temp:	-40°C--50°C
Storage Temp;	-60°C--80°C
Humidity:	30%--85%

Product Details:



Relevant documents:

Do you want to know more product information?Please Click here.

- [Specification](#)
- [User Manual](#)
- [Driver](#)

