

Printers for direct barcode labels (Model: OCBP-005)

Features:

- Label paper auto position;
- Labels peel off automatically;
- Adjust the printer head pressure;
- Compatible with plenty of label software;
- BMP, PCX, BAC images download store;
- Support Serial, USB, LAN together;
- Support PDF417, QR CODE, DOTMATRIX;

Technical specifications:

Printer model	OCBP -005
Resolution	203 DPI (8 points / mm)
Printing method	Direct thermal
Head temperature sensor	Thermal varistor
Head sensor pos	microswitch
Card detection	Photoelectric sensors
Print speed	127 Mm / sec (maximum); 50.8 mm / sec (minutes)
Print width	16 mm to 82 mm
Average	Media type: roll, stickers, folding labels and so on. Diameter of the support: inner diameter: 25 mm; diameter: 80 mm
Internal font	Typeface 0 FONT 8; commonly used in single-byte characters
Enlarge & Rotating	Amplification 1-10 times in multiple directions; 0 degrees, 90 degrees, 180 degrees, 270 degrees, 360 degrees rotation
Out of the type of paper	Lacrima and & peeling
Memory cards	2 MB FLASH ROM, 2 MB of DRAM
Image	Monochrome PCX, BMP pos image files are loaded in FLASH, DRAM
Barcode	CODE128, EAN128, ITF, Code39, Code93, EAN13, EAN13 +2, EAN13 +5, EAN8, EAN8 +2, EAN8 +5, CODABAR, POS TNET, UPC-A, UPCA +2, UPCA +5, UPC-E , UPCE +2, UPCE +5, C POS T, MSI, MSIC, PLESSEY, ITF14, EAN14, PDF417, QR CODE, DATMATRIX
Interface	USB + RS232 + LAN or USB
Power	Input: 24 VDC, 2.5 A

Environment	Operating temperature: from 5 ° C to 45 ° C Storage temperature: from -40 ° C to 55 ° C Operating humidity: 20% ~ 80%, without condensation, free air Storage humidity: & lt; = 93% (40 ° C), without condensation, free air
Dimension	Dimensions: D220mm * H148mm * W150mm

Different Angle:



Paper Loading:



Production Pictures Show



OCBP-005



Support 4GB DRAM, 4GB NV FLASH
5 INCHES HIGH SPEED PRINTING

- Thermal transfer printer
- Supports 4GB DRAM and 4GB NV FLASH
- Supports 5 INCHES HIGH SPEED PRINTING
- Supports 4GB DRAM, 4GB NV FLASH
- Supports 5 INCHES HIGH SPEED PRINTING





OCBP-005





OCBP-005





OCBP-005





OCBP-005

