

2 inch Thermal Label Barcode Printer with USB Interface

(M/N:OCBP-006)

- 1.Support thermal roll paper / adhesive paper
- 2.The print head with adjustable pressure
- 3.Automatic paper checking function
- 4.Temperature adaptive control
- 5.Modular design, to meet different application requirements

label printing machine,barcode label thermal printer,direct thermal label printer

Printing method	Direct thermal
Resolution	203DPI
Print width	20-60mm
Printing speed	MAX:127mm/s]MIN:50.8mm/s
Memory	DRAM: 4M FLASH: 4M
Print head temperature	Thermistor
Paper exists detection	The micro switch
Interface	USB
Paper presence detection	Paper presence detection
Barcode	CODE128]EAN128]ITF]CODE39]CODE93]EAN13]EAN13+2]EAN13+5]EAN8]EAN8+2]EAN8+5]CODABAR]POSTNET]UPC-A]UPCA+2]UPCA+5]UPC-E]UPCE+2]UPC-E+5]CPOST]MSI]MSIC]PLESSEY]ITF14]EAN14 Qrcode] DM Code] PDF417
Internal font	FONT 0 to FONT 8
Enlargement & rotation	0°~90°~270°~360° 1 to 10 times enlargement in both direction; 0°~90°~270°~360° rotation
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM
Paper type	Paper roll, sticker, adhesive sticker, etc
Paper width	20mm~60mm
Roll external	MAX 80mm
Roll inner diameter	MIN 25mm
Paper off type	Tear off
Power supply input	DC12V, 3A
Weight	1.04KG
Dimensions	190(D) x 135(W) x 137(H)mm
Work environment	5~45°C, 20~80%RH(no condensation)
Storage environment	-40~55°C]≤93%RH]40°C]

Relevant documents:

[Driver and CD files](#)