

3 Inch Direct Thermal Bar Code Label Printer with Auto Cutter

(M/N:OCBP-015)

Features

- Support 8 kinds abundant interface combination;
- Support TSPL and ECS/POS Command;
- Support Manual tear and Auto-cutter;
- Supports multi 1D barcode and 2D code printing;
- Support printer status monitoring function;
- 100M Ethernet port, ultra high speed data transmission;
- 2MB big DRAM And 2MB buffer memory;
- Standard 25 to 80mm adjustable Paper separator;
- 150KM long life printer head.

Technical parameters

| | |
|-----------------------|---|
| Print Method | Direct Thermal |
| Command | TSPL and ESC/POS (can change by end user) |
| Resolution | 203dpi ,576dots/line |
| Printing Width | Max=72mm |
| Paper Type | Thermal label printer or continuous receipt Paper |
| Interface | USB/UR/UL/URL/U+BT/ U+WIFI/URL+BT/URL+WIFI |
| Print Speed | Max=152mm/s for label, MAX=260mm/s for receipt mode |
| Paper Width | 20mm-80mm |
| Paper Thickness | 0.06~0.19mm |
| Roll Dia | Max. Ø 83 mm |
| Paper Cut | Manual tear and Auto-cutter |
| DRAM | 2MB |
| Flash | 2MB |
| Font Size | font A:12*24(standard), font B:9*17 |
| Chinese | GB18030,BIG5 24x24dots |
| Japanese/Korea | Support |
| User-defined language | PC347(Standard Europe),Katakana,PC850(Multilingual),PC860(Portuguese),PC863(Canadian-French),PC865(Nordic),West Europe,Greek,Hebrew,East Europe,Iran,WPC1252,PC866(Cyrillic#2),PC852(Latin2),PC858,IranII,Latvian,Arabic,PT151(1251) ect. |
| 1D | UPC-A/UPC-E/JAN13[EAN13]/JAN8 [EAN8]/CODE39/ITF/CODABAR/CODE93/CODE128/MSI/ITF-14/CPOST/PLESSEY,etc. |
| 2D | QR,PDF417, DM |
| Printing head life | 150 KM |
| Cutter life | 1million |
| Paper separator | Standard |
| Sensors | Paper out, cover open, cutter jam,paper jam and black mark detection |
| Input | AC 100V-240V 50/60HZ |
| Output | DC 24V/2.5A |
| Working Condition | 0°C~45°C, 10%~80%RH |

| | | |
|-------------------|---|----------------|
| Storage Condition | -10°C-60°C,10%~90%RH | |
| Accessories | Data cable, power adaptor, power code, paper roller, CD, manual, Paper separator (standard) | |
| Dimensions | 196(D)x145(W)x135(H)mm | |
| Net weight | 1.14kg | |
| Gross weight | 1.5kg | |
| Individual box | Dimension 30X19X18cm(LXWXH) | 1unit/carton |
| Master carton | Dimension 62X36X52cm(LXWXH) | 12units/carton |
| Driver | Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS | |
| SDK | Android, IOS | |





OCBP-015





OCBP-015





OCBP-015





OCBP-015







Relevant documents:

[OCBP-015 SPEC](#)

[OCOM Label Printer Software and Driver](#)