

# Direct Thermal Bar Code Label Printer

## □(OCBP-020)

### Features:

1. Printing Width can be adjustable
2. Intelligent temperature controlling makes printer work more stably
3. Automatic calibration
4. Highly printing speed
5. Compatible with various shipping labels

### Specification

|  |   |
|--|---|
| <b>Model</b>                             | OCBP-020  |
| <b>Interface</b>                         | USB/USB+Bluetooth/USB+LAN   |
| <b>Printer Head life</b>                 | 50KM  |
| <b>Power adaptor</b>                     | Input□AC 100-240V, 50□60Hz ; Output□DC 24V/1.5A   |
| <b>Sensors</b>                           | Dual-media sensors: transmissive and reflective   |
| <b>Printer driver</b>                    | Windows, MAC OS , Support IOS / Android   |
| <b>Font and barcode rotation</b>         | 0°,90°,180°,270°  |
| <b>Printer command</b>                   | TSPL command (CPCL/ESC/POS command-optional)  |
| <b>Printing method</b>                   | Direct line thermal   |
| <b>Resoluiton</b>                        | 203 DPI   |
| <b>Print speed</b>                       | 120mm/s   |
| <b>Print width</b>                       | 20-76mm   |
| <b>Available Max Paper Width</b>         | 80mm  |
| <b>Barcode</b>                           | 1D barcode:<br>UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128<br>2D barcode: QR Code, PDF417 |
| <b>Media</b>                             |   |
| <b>Media type</b>                        | continuous paper, label paper, folded paper, tag paper  |
| <b>Media width</b>                       | Max 80mm  |
| <b>Media thickness</b>                   | 0.06-0.30 mm  |
| <b>Media core diameter</b>               | 25.4mm  |
| <b>Paper roll diameter</b>               | 100mm (MAX)   |
| <b>Physical</b>                          |   |
| <b>Physical dimension</b>                | 200*160*139.5mm   |
| <b>Weight</b>                            | Net:1.02kg , Gross1.40kg  |
| <b>Package box</b>                       | 235*220*170mm   |
| <b>8 in one carton</b>                   | 490*460*360mm/12kg  |
| <b>Accessories</b>                       | USB cable,User Manual,Power adaptor   |
| <b>Environment</b>                       |   |
| <b>Working temperature&amp; humidity</b> | 5 to 40 degrees centigrade, 25%~85% No condensation   |
| <b>Storage temperature&amp; humidity</b> | -40 to 60 degrees centigrade , 10%~90% No condensation  |













