

Direct Thermal Bar Code Label Printer

□OCBP-020)

Features:

1. Printing Width can be adjustable
2. Intelligent temperature controlling makes printer work more stably
3. Automatic calibration
4. Highly printing speed
5. Compatible with various shipping labels

Specification

Model	OCBP-020
Interface	USB/USB+Bluetooth/USB+LAN
Printer Head life	50KM
Power adaptor	Input□AC 100-240V, 50□60Hz ; Output□DC 24V/1.5A
Sensors	Dual-media sensors: transmissive and reflective
Printer driver	Windows, MAC OS , Support IOS / Android
Font and barcode rotation	0°,90°,180°,270°
Printer command	TSPL command (CPCL/ESC/POS command-optional)
Printing method	Direct line thermal
Resoluiton	203 DPI
Print speed	120mm/s
Print width	20-76mm
Available Max Paper Width	80mm
Barcode	1D barcode: UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 2D barcode: QR Code, PDF417
Media	
Media type	continuous paper, label paper, folded paper, tag paper
Media width	Max 80mm
Media thickness	0.06-0.30 mm
Media core diameter	25.4mm
Paper roll diameter	100mm (MAX)
Physical	
Physical dimension	200*160*139.5mm
Weight	Net:1.02kg , Gross1.40kg
Package box	235*220*170mm
8 in one carton	490*460*360mm/12kg
Accessories	USB cable,User Manual,Power adaptor
Environment	
Working temperature& humidity	5 to 40 degrees centigrade, 25%~85% No condensation
Storage temperature& humidity	-40 to 60 degrees centigrade , 10%~90% No condensation













