

2 Inch Direct Thermal Label Printer

(M/N:OCBP-201)

- v USB or USB+Bluetooth Interface for optional
- v Automatic paper checking function
- v Temperature adaptive control
- v Support receipt mode and label mode switching
- v Compatible with TSPL and ESC/POS command
- v Compact and sleek design for stylish counters

Printing method	Direct thermal
Resolution	203DPI
Command	TSPL and ESC/POS
Mode switching	Support receipt mode and label mode switching (Command:HEX:1F 1B 1F 02 20 n 0D 0A,n=31/30,default n=30)
Print width	20-60mm
Printing speed	MAX:101mm/s;MIN:50.8mm/s
Memory	DRAM: 256kb FLASH: 576kb
Printhead temperature	Thermistor
Paper exists detection	Micro switch
Interface	USB orUSB+Bluetooth
Paper presence detection	Paper presence detection
Barcode	CODE128,EAN128,ITF,CODE39,CODE93,EAN13,EAN13+2,EAN13+5,EAN8,EAN8+2,EAN8+5,CODABAR,POSTNET,UPC-A,UPCA+2,UPCA+5,UPC-E,UPCE+2,UPC-E+5,CPOST,MSI,MSIC,PLESSEY,ITF14,EAN14 Qrcode, DM Code, PDF417
Enlargement & rotation	(0°,90°270°, 360°) 1 to 10 times enlargement in both direction; 0°,90°,270°, 360° rotation
Image	Monochromatic PCX, BMP image files can be load to FLASH
Paper type	Paper roll, sticker, adhesive sticker, etc
Paper width	20mm~60mm
Roll external	MAX 80mm
Roll inner diameter	MIN 25mm
Paper off type	Tear off
Power supply input	DC12V, 3A
Work environment	5~45°C, 20-80%RH(no condensation)
Storage environment	-40~55°C, ≤93%RH(40°C)



OCBP-201





OCBP-201





OCBP-201

