

4-inch Thermal Barcode Label Printer

(M/N: OCBP-401DT)



Features:

More economics□

Built-in dual sensors ensure no paper waste when loading paper.

Easy to operate□

DHCP function makes the printer plug-and-play, No more complicated IP address settings.

More durable:

10W big motor and big gear, make the service life longer.

High-end materials:

Japanese ROHM Printer head, the printing life is up to 50km.

Smarter editing software□

IOS+Android+Harmony OS +Windows+MAC, five-terminal interoperable free editing software.

Specification

General	
Model	OCBP-401DT
Material	Plastic housing
Optional interface	USB+BT+WIFI
Connection	Computer, tablet, mobile phone
Processor	32-bit CPU
Memory	4MB Flash Memory, 320KB RAM
Printer Head life	50 KM
MTBF	4000 h
Power supply	Input wide range voltage AC 100V-250V 50-60Hz Output 24VDC
Accessories	Power adapter, Power cable, USB cable, Label shaft, Manual
Sensors	Label edge detection, Label size detection, Out of paper detection, Gap detection, Black-mark detection, Cover-open detection
Gap height	2 mm Min
Black-mark height	2 mm Min
Font and bar code rotation	0°, 90°, 180°, 270°
Compatible command	TSPL
Driver	Windows, Linux, Mac
SDK	Windows, Linux, Mac, IOS, Android
Printing capability	
Printing method	Direct Thermal
Resolution	203 DPI
Print speed	152 mm/s max
Print width	20-108 mm
Label print length	10-250 mm
Barcode and character	
Bar-code	1D bar code: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D bar code: PDF417, Maxi code, Data Matrix, QR code
Font	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software
Media	
Paper type	Folded paper or roll paper, die-cut label, black mark paper, direct thermal decal label paper (no ink required)
Paper width	20-118 mm
Paper thickness	0.06-0.22 mm
Label roll capacity	127 mm OD (outside wound)
Core inner	~1 inch (24 mm)
Physical	
Dimension	232mm*180mm*152mm (LWH)
Weight	1.36 kg
Package box	254mm*254mm*174mm/ 1.92Kg
8 in 1 carton	528mm*528mm*368mm/ 15.36kg
Environment	
Working temperature & humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 50 degrees centigrade, 10%~90% No condensation

Thermal Barcode Label Printer

Model: OCBP-401DT



Multi-System Compatible

IOS+Android+HarmonyOS+Windows(Win xp,7,8,10,11)+MAC
five-terminal interoperable free editing software

