

4 Inches Direct Thermal Barcode Label Printer

□Model: OCBP-402DT)

Features:



More economics□

Built-in dual sensors ensure no paper waste when loading paper.

Easy to operate□

DHCP function make the printer plug-and-play, No more complicated IP address settings.

More durable:

42mm 10W high torque motor, more powerful and longer service life.

High-end materials:

Japanese ROHM Printer head, the printing life is up to 50km.

Smarter editing software

IOS+Android+HarmonyOS+Windows+MAC five-terminal interoperable free editing software.

Specification

General	
Model	OCBP-402DT
Material	Plastic housing
Interface	USB, USB+Bluetooth, USB+Bluetooth+WIFI, USB+LAN
Processor	32 bit CPU
Memory	4MB Flash Memory, 320KB RAM
Printer Head life	50Km
Power supply	Input: AC 100V-240V, 50-60Hz, Output: DC 24V/2.5A
Accessories	Power adapter, Power cable, USB cable, Manual, outside bracket for option
Sensors	Label edge detection, Out of paper detection, Gap detection, Black mark detection, Cover-open detection
Gap height	2mm Min
Black-mark height	2mm Min
Font and bar-code rotation	0°, 90°, 180°, 270°
Compatible command	TSPL
Printing capability	
Printing method	Direct Thermal
Resolution	203 DPI
Printing speed	152mm /s Max
Printing width	30-108mm
Printing length	10-250mm
Bar-code and character	
Bar-code	1D bar code: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Coda bar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D bar code: PDF417, Maxi code, Data Matrix, QR code
Font	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software
Media	
Paper type	Folded paper or roll paper, die-cut label, black mark paper
Paper width	30-118mm
Media thickness	0.06 ~ 0.22mm
Physical	
Dimension	220*112*102mm

Weight	Net: 1.02kg
Package box	248*140*170mm/1.87Kg
8 in 1 carton	516*300*360mm /12.4kg
Environment	
Working temperature & humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature & humidity	-20 to 60 degrees centigrade , 10%~90% No condensation

THERMAL SHIPPING LABEL PRINTER

OEM/ODM

COMPLETE QUALIFICATION SUPPORT CUSTOMIZATION



Thermal label printer

Works Perfectly for 4x6 Labels



OCBP-402DT

Media type: Roll label/fanfold

Printing width: 30-108mm

Printing speed: 50-152mm/s

Both stacked and rolled labels can be printed



Print roll label



Print stacked labels

Durable & Cost Saving

1. Thermal Label Printer applies newest direct thermal printing technology.
2. About 1 second to print one 4"x6" shipping label.
3. Save time and money in your shipping and storage.



Multi-System Compatible

Label Printer can smoothly run on Windows XP, 7, 8,10, Mac OS.
Please choose Bluetooth version and download Soonmark APP
to print labels through your smart phones.



Windows 10



Windows 8



Windows 7



Windows XP



Mac OS



(Note: NOT compatible with Chrome OS).

Multi-Size Compatible

*This printer provides adjustable paper guide rail
for small companies, enable them to print various sizes of labels
with width range from **20-118mm***



Media width

|———— 118mm ———|

Printer Internal Components



OCBP-402DT TECH SPECS



Driver support

Windows XP,7, 8,10,
Mac OS



Printing Method

Direct Thermal



Resolution

203 dpi



CPU

32-bit RISC CPU



RAM

8MB



Flash

4MB



Printing Speed

50-152 mm/s



Printing Width

20-108mm



Printing Length

25-300mm



Media Type

Folded paper,
roll paper,
die-cut label,
black mark paper



Media Width

20-118mm



Media Thickness

60μm-220μm



Interfaces

Default
USB



Programming

Language
TSPL



Control Panel

One Feed button
(three colors for
three different status)



Power Adapter

Input: AC 100-240V,
1A,50-60Hz
Output: DC 24V,2.5A,60W



Dimension (WHD)

220*112*102



Weight

1.17kg

Packing List (default)







99

P
PRIORITY MAIL 2-DAY™



SHIP TO:
DO NOT SHIP
11 CAMPBELL AVE
CAMPBELL CA 95009

John Smith
1234 BARNES RD
CARSON NY 30000

06250009999642
769597
FROM 99610

SAMPLE LABEL
6 LB PRIORITY MAIL RATE
ZONE 4 NO SURCHARGE
COMMERCIAL PLUS PRICING











Relevant documents:

[OCBP-402DT Driver](#)

[OCBP-402DT Label editing software - Android](#)

[OCBP-402DT Label editing software - IOS](#)

[OCBP-402DT Label editing software - Mac OS](#)

[OCBP-402DT Label editing software - Windows](#)