

4 Inches Direct Thermal Barcode Label Printer

Model: OCBP-403DT)

Features:



Various interface and capabilities;

Bluetooth support android and IOS;

Easy paper loading;

High printing speed.

Specification

General	
Model	OCBP-403DT
Material	Plastic housing
Optional Interface	USB / USB+Bluetooth / USB+LAN
Printer Head life	50 KM
Power supply	Input AC 100V-240V, 50-60Hz, Output DC 24V/2.5A
Accessories	Power adapter, USB cable, Manual
Sensors	Without paper, low power, cover open
Gap height	2mm Min
Black-mark height	2mm Min
Font and bar code rotation	0°, 90°, 180°, 270°
Compatible command	TSPL
Printing capability	
Printing method	Direct Thermal
Resolution	203 DPI

Print speed	Up to 140mm/s
Print width	20-108mm
Label print length	25-250 mm
Barcode and character	
text and graphic Support	CODE39, EAN13, EAN8, CODABAR, CODE128, CODE93, ITF English, figure, symbol, Chinese, graph, icon pre-stored
Media	
Paper type	Folded paper or roll paper, die-cut label, black mark paper
Paper width	25.4-114mm
Paper thickness	0.06-0.22mm
Label roll capacity	100 mm OD (outside wound)
Physical	
Dimension	210mm*175mm*148mm
Weight	Net: 1.17 kg
Package box	248*229**169mm/1.73Kg
4 in 1 carton	480*265*365mm/7.6kg
Environment	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 50 degrees centigrade, 10%~90% No condensation

