2 Inch Industrial Grade Bluetooth Thermal Printer (Model Number: OCBP- M18)

Features:

- n Mini size suitable for portable application;
- n Provide Android App more suitable for end users;
- n Compatible with bartender software
- n Support label interval sensor
- n Can change the printer name, password, baud rate online;
- n 50mm diameter paper warehouse;
- n Loading paper width can be adjusted
- n Support Voice Input /Graphic Recognition/Scanning Recognition and other functions
- n Compatible with Android and IOS
- n Can Print 5 hours continuously, 7 days long standby time
- n 90mm/sec print speed;
- n Support ESC/POS,JPL,TSPL,CPCL, 4 kinds of command;
- n 360 overall protection, Shock-resistant designs
- n IP54 Grade, Support Printing in Rainy days and outdoor.

Specification:

max 6 digitals. Weight Net weight:0.4kg/Set, Gross weight:0.7kg/Set		
Effective print widthMax=48mm,384 dotsPrint speedUp to 90mm/secResolution8 dots/mm(203dpi)Paper dimensions57.5.±0.5mm x diameter 50.0mmPaper thickness0.06 to 0.12mmCharacter setAlphanumeric/ ChineseInterfaceUSB,and BluetoothFlash256KBPower Adapter9V DC/1ACharging time4-5 hoursBattery Power1200mAh,7.4VWorking time5 hours continuously, 7 days standby timePrinter head life50KMOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%~90%Storage conditionsTemperature:-20~70 degC, Humidity:10%~95%Device nameCan be customized, letter and digital for option, at max 30 ASCII characters.PasswordEnter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals.WeightNet weight:0.4kg/Set, Gross weight:0.7kg/Set	Print method	Thermal line printing
Print speedUp to 90mm/secResolution8 dots/mm(203dpi)Paper dimensions57.5.±0.5mm x diameter 50.0mmPaper thickness0.06 to 0.12mmCharacter setAlphanumeric/ ChineseInterfaceUSB,and BluetoothFlash256KBPower Adapter9V DC/1ACharging time4-5 hoursBattery Power1200mAh,7.4VWorking time5 hours continuously, 7 days standby timePrinter head life50KMOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%~90%Storage conditionsTemperature:-20~70 degC, Humidity:5%~95%Device nameCan be customized, letter and digital for option, at max 30 ASCII characters.PasswordEnter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals.WeightNet weight:0.4kg/Set, Gross weight:0.7kg/Set	Print commands	ESC/POS,TSPL,JPL command
Resolution8 dots/mm(203dpi)Paper dimensions57.5.±0.5mm x diameter 50.0mmPaper thickness0.06 to 0.12mmCharacter setAlphanumeric/ ChineseInterfaceUSB,and BluetoothFlash256KBPower Adapter9V DC/1ACharging time4-5 hoursBattery Power1200mAh,7.4VWorking time5 hours continuously, 7 days standby timePrinter head life50KMOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%~90%Storage conditionsTemperature:-20~70 degC, Humidity:5%~95%Device nameCan be customized, letter and digital for option, at max 30 ASCII characters.PasswordEnter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals.WeightNet weight:0.4kg/Set, Gross weight:0.7kg/Set	Effective print width	Max=48mm,384 dots
Paper dimensions57.5.±0.5mm x diameter 50.0mmPaper thickness0.06 to 0.12mmCharacter setAlphanumeric/ ChineseInterfaceUSB,and BluetoothFlash256KBPower Adapter9V DC/1ACharging time4-5 hoursBattery Power1200mAh,7.4VWorking time5 hours continuously, 7 days standby timePrinter head life50KMOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%~90%Storage conditionsTemperature:-20~70 degC, Humidity:5%~95%Device nameCan be customized, letter and digital for option, at max 30 ASCII characters.PasswordEnter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals.WeightNet weight:0.4kg/Set, Gross weight:0.7kg/Set	Print speed	Up to 90mm/sec
Paper thickness0.06 to 0.12mmCharacter setAlphanumeric/ ChineseInterfaceUSB,and BluetoothFlash256KBPower Adapter9V DC/1ACharging time4-5 hoursBattery Power1200mAh,7.4VWorking time5 hours continuously, 7 days standby timePrinter head life50KMOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%~90%Storage conditionsTemperature:-20~70 degC, Humidity:5%~95%Device nameCan be customized, letter and digital for option, at max 30 ASCII characters.PasswordEnter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals.WeightNet weight:0.4kg/Set, Gross weight:0.7kg/Set	Resolution	8 dots/mm(203dpi)
Character setAlphanumeric/ ChineseInterfaceUSB, and BluetoothFlash256KBPower Adapter9V DC/1ACharging time4-5 hoursBattery Power1200mAh, 7.4VWorking time5 hours continuously, 7 days standby timePrinter head life50KMOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%~90%Storage conditionsTemperature:-20~70 degC, Humidity:5%~95%Device nameCan be customized, letter and digital for option, at max 30 ASCII characters.PasswordEnter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals.WeightNet weight:0.4kg/Set, Gross weight:0.7kg/Set	Paper dimensions	57.5.±0.5mm x diameter 50.0mm
InterfaceUSB,and BluetoothFlash256KBPower Adapter9V DC/1ACharging time4-5 hoursBattery Power1200mAh,7.4VWorking time5 hours continuously, 7 days standby timePrinter head life50KMOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%~90%Storage conditionsTemperature:-20~70 degC, Humidity:5%~95%Device nameCan be customized, letter and digital for option, at max 30 ASCII characters.PasswordEnter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals.WeightNet weight:0.4kg/Set, Gross weight:0.7kg/Set	Paper thickness	0.06 to 0.12mm
Flash256KBPower Adapter9V DC/1ACharging time4-5 hoursBattery Power1200mAh,7.4VWorking time5 hours continuously, 7 days standby timePrinter head life50KMOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%~90%Storage conditionsTemperature:-20~70 degC, Humidity:5%~95%Device nameCan be customized, letter and digital for option, at max 30 ASCII characters.PasswordEnter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals.WeightNet weight:0.4kg/Set, Gross weight:0.7kg/Set	Character set	Alphanumeric/ Chinese
Power Adapter9V DC/1ACharging time4-5 hoursBattery Power1200mAh,7.4VWorking time5 hours continuously, 7 days standby timePrinter head life50KMOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%~90%Storage conditionsTemperature:-20~70 degC, Humidity:5%~95%Device nameCan be customized, letter and digital for option, at max 30 ASCII characters.PasswordEnter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals.WeightNet weight:0.4kg/Set, Gross weight:0.7kg/Set	Interface	USB,and Bluetooth
Charging time4-5 hoursBattery Power1200mAh,7.4VWorking time5 hours continuously, 7 days standby timePrinter head life50KMOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%~90%Storage conditionsTemperature:-20~70 degC, Humidity:5%~95%Device nameCan be customized, letter and digital for option, at max 30 ASCII characters.PasswordEnter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals.WeightNet weight:0.4kg/Set, Gross weight:0.7kg/Set	Flash	256KB
Battery Power 1200mAh,7.4V Working time 5 hours continuously, 7 days standby time Printer head life 50KM Other features Paper detection, manual shut down Working conditions Temperature:-10~50 degC, Humidity:10%~90% Storage conditions Temperature:-20~70 degC, Humidity:5%~95% Device name Can be customized, letter and digital for option, at max 30 ASCII characters. Password Enter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals. Weight Net weight:0.4kg/Set, Gross weight:0.7kg/Set	Power Adapter	9V DC/1A
Working time5 hours continuously, 7 days standby timePrinter head life50KMOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%~90%Storage conditionsTemperature:-20~70 degC, Humidity:5%~95%Device nameCan be customized, letter and digital for option, at max 30 ASCII characters.PasswordEnter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals.WeightNet weight:0.4kg/Set, Gross weight:0.7kg/Set	Charging time	4-5 hours
Printer head life 50KM Other features Paper detection, manual shut down Working conditions Temperature:-10~50 degC, Humidity:10%~90% Storage conditions Temperature:-20~70 degC, Humidity:5%~95% Device name Can be customized, letter and digital for option, at max 30 ASCII characters. Password Enter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals. Weight Net weight:0.4kg/Set, Gross weight:0.7kg/Set	Battery Power	1200mAh,7.4V
Other featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%~90%Storage conditionsTemperature:-20~70 degC, Humidity:5%~95%Device nameCan be customized, letter and digital for option, at max 30 ASCII characters.PasswordEnter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals.WeightNet weight:0.4kg/Set, Gross weight:0.7kg/Set	Working time	5 hours continuously, 7 days standby time
Working conditions Temperature:-10~50 degC, Humidity:10%~90% Storage conditions Temperature:-20~70 degC, Humidity:5%~95% Device name Can be customized, letter and digital for option, at max 30 ASCII characters. Password Enter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals. Weight Net weight:0.4kg/Set, Gross weight:0.7kg/Set	Printer head life	50KM
Storage conditions Temperature:-20~70 degC, Humidity:5%~95% Device name Can be customized, letter and digital for option, at max 30 ASCII characters. Password Enter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals. Weight Net weight:0.4kg/Set, Gross weight:0.7kg/Set	Other features	Paper detection, manual shut down
Device name Can be customized, letter and digital for option, at max 30 ASCII characters. Password Enter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals. Weight Net weight:0.4kg/Set, Gross weight:0.7kg/Set	Working conditions	Temperature:-10~50 degC, Humidity:10%~90%
Password Enter default pairing code "1234", it can be customized or change by customer itself. A max 6 digitals. Weight Net weight:0.4kg/Set, Gross weight:0.7kg/Set	Storage conditions	Temperature:-20~70 degC, Humidity:5%~95%
max 6 digitals. Weight Net weight:0.4kg/Set, Gross weight:0.7kg/Set	Device name	Can be customized, letter and digital for option, at max 30 ASCII characters.
Weight Net weight:0.4kg/Set, Gross weight:0.7kg/Set	Password	Enter default pairing code "1234", it can be customized or change by customer itself. At
		· · · ·
Single box size 13.5*13.5*11cm	Single box size	13.5*13.5*11cm

