(ModelNumber: OCBP- M58)

\mathbf{T}				
н	ea	tı.	ırc	20
1	Cα	ıν	ıιτ	7.7

- n Support Windows, Java, Android OR iPhone OS.
- n Bluetooth, USB communication for option.
- n Higher print speed 90mm/sec.
- n 100km TPH Life.
- n Low power consumption and large capacity Lithium battery.

Specification:

Overall Dimension $(W \times D \times H)$	195×134×55mm,585*410*285mm(40pcs)	
Weight	0.45kg,20kg(40pcs)	
Color	Black	
Effective print width	48mm	
Print method	Thermal line printing	
Print commands	ESC/POS compatible command set	
Print speed	Up to 90mm/sec	
Resolution	8 dots/mm(203dpi)	
Print font	12x24/ 24x24	
Column capacity	32 columns/ 16columns	
Character size	1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)	
Paper dimensions	58.0±0.1mm x diameter 40.0mm	
Paper thickness	0.06 to 0.08mm	
Character set	Alphanumeric/ Chinese Kanji	
Interface	USB, RS-232∏Bluetooth (optional)	
Data buffer	Up to 5K bytes	
Power Adapter	9V DC/1A	
Battery Power	1300mAh/7.4V,	
	30m printing for one charging, longer stand-by time up to 30days	
Other features	Paper detection, power detection, Manual shut down	
Working conditions	Temperature:-10°C□50°C,Humidity:10%□90%	
Storage conditions	Temperature:-20°C[]70°C,Humidity:5%[]95%	
Device name	Can be customized, letter and digital for option, at max 30 ASCII characters.	
Password	Enter default pairing code "1234", it can be customized. At max 6 digitals.	

Power plug dimension	3.5*1.1mm