

# (OCBP-M88)Thermal Receipt Printer 80MM Direct Wireless Pocket Hand Held Thermal Barcode Transfer Label Sticker Printer

(M/N:OCBP-M88)

## Features:

Front paper output structure makes paper feed smoother and less jams

Fully body TPU wrap,strong anti-drop performance

Support label interval sensor

The width of the paper bin can be adjusted

50 diameter paper roller can be installed

The USB Type-C interface can be both charge and communication

The LCD screen can directly observe the printer status

Support the physical button to set the printer

Free label editing software,convenient for end users to use directly

## Specification:

| General                       |                                                                                                           |
|-------------------------------|-----------------------------------------------------------------------------------------------------------|
| Model                         | OCBP-M88                                                                                                  |
| Color                         | Gray and white                                                                                            |
| Processor                     | 32 bit CPU                                                                                                |
| Interface                     | USB type-C and Bluetooth                                                                                  |
| Printer head life             | 100Km                                                                                                     |
| Battery                       | 2600mAh, 7.4V 15Wh Non-removable battery                                                                  |
| Charging time                 | 4-5 hours                                                                                                 |
| screen                        | 1 inch TFT color screen                                                                                   |
| Sensors                       | Gap sensor,Cover opening sensor,Black mark sensor,Overheating sensor,paper end sensor                     |
| Working time                  | 200meter printing, 7 days standby time                                                                    |
| Power supply                  | 5V DC/1A                                                                                                  |
| Memory                        | 8MB                                                                                                       |
| software                      | Windows/Android/IOS/MAC                                                                                   |
| Safety standards              | CE ,FCC,Rohs etc                                                                                          |
| Printing capability           |                                                                                                           |
| Printing method               | Direct Thermal                                                                                            |
| Resoluiton                    | 8 dots/mm(203 DPI)                                                                                        |
| Print speed                   | 80mm/s                                                                                                    |
| Print width/ length           | 72mm Max/ 1778mm Max                                                                                      |
| Print command                 | ESC/POS, CPCL command                                                                                     |
| Barcode and character         |                                                                                                           |
| Barcode                       | EAN-8, EAN-13, ITF, UPC-A, UPC-E, Codebar, Code93, Code39, Code128,QR Code,PDF417,Data Matrix,Grid Matrix |
| Character set                 | Alphanumeric/ GBK/Unicode                                                                                 |
| Media                         |                                                                                                           |
| Media type                    | Continuous,Gap, Black mark                                                                                |
| Media width                   | 15-80mm                                                                                                   |
| Media thickness               | 0.05-0.18mm                                                                                               |
| Media roll diameter           | 50mm Max                                                                                                  |
| Physical                      |                                                                                                           |
| Dimension                     | 102mm*113mm*57mm                                                                                          |
| Weight/Package box            | Net:390g Gross:531.3g/192.5×129.4×63.8mm                                                                  |
| 16 in 1 carton                | 384×345×295mm/10kg                                                                                        |
| Environment                   |                                                                                                           |
| Working temperature&humidity  | 0 to 45 degrees centigrade, 10%~80% No condensation                                                       |
| Storage temperature& humidity | -20 to 60 degrees centigrade , 10%~90% No condensation                                                    |

## Product overview:

















