

# China high speed One Dimensional CCD Barcode Scanner

## (Model:OCBS-C005)

### Product Description

#### Description:

This BarCode Scanner can plug and play, no need to install software.

Efficient decoding rate and ultra-low error rate.

It can accurately and quickly scan a variety bar code in the strong light and dark environment.

#### Features

- The fast scan speed reach up to 300 times/second.
- 3 mil excellent scanning accuracy.
- Efficient decoding rate and ultra-low error rate. Many kinds of one-dimensional bar code can be identified.
- Support reading bar codes from screen.
- No driver, plug and play.
- High resilient button: Use high rebound button, accurate limit, durable.
- Scanning Mode Setting:Manual trigger and Auto Scanning and Continue Scanning.
- Support multiple data interfaces: USB-HID, USB virtual port, UART, KB, HID-POS, etc.
- Support 16 country language.
- Adopt a highly integrated design, high quality shell, have IP45 protection grade, 5m height fall many times, still can be used normally.
- Application fields:Supermarket, Retail, Warehouse,Logistic,Library, Medical etc.
- Can be customized according to customer demand.

#### Scanner parameters:

Light source type		Optical Imaging; the wave length is 632mm.
Imaging sensor		linear imaging sensor(CCD)
Pixel resolution		2500 pixels
Barcode precision		≥ 3mil
Printing Contrast Ratio		≥ 30%
Barcode type		UPC/EAN/JAN, UPC/EAN with Supplemental, UCC/EAN 128, Code 39, MSI, Code11, Code 39 Full ASCII, Code 39 TriOptic, Code 128, Code 128Full ASCII, EAN-13, EAN-8, UPC-A, UPC-E, ISBN, Code 93, GS1 Databar, Codabar, Code93, Discrete2of5, IATA, RSSvariants, Codabar, Chinese2of5, International general dimensional barcodes, e.g. Inteleaved2/5, Interleaved2of5,China postal service code and so on
Scanning speed		300times/s
Scanning angle	Clockwise/anticlockwise	±55°
	Up and down	±25°
	Left and right	±75°
External dimensions(L x W x H)		165×65×97 mm
Weight		190g
prompting Mode		Buzzer and LED indicator
Maximum power consumption		650mw
Working voltage		DC5V
Electric current	Maximum current	130ma
	Working current	86ma
	Standby current	42ma

Accessories	
Cable	RS232/USB data cable(1.8m)
Manual	1
Environment	
Storage temperature	-40°C ~ 60°C
Work temperature	0°C ~ 50°C
Relative humidity	0 ~ 95%
Anti-knock	working fine after fall from 5m height

## ► Picture Show



# OCBS-C005





OCBS-C005





OCBS-C005





OCBS-C005





OCBS-C005







OCBS-C005



## ► Application scenario

Logistics



Warehouse management



Supermarket



Clothing label



Jewelry label



Restaurant





## ► Company



## ► Certificates



## ► Payment



## ► Contact us



Monica Fu



## OCOM Technologies Limited

---

**Add:** 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

**Tel:** 0086.755.8605.3207 ext 801

**Fax:** 0086.755.8605.3207 ext 868

**Web:** [www.ocominc.com](http://www.ocominc.com)

**E-mail:** [sales01@ocominc.com](mailto:sales01@ocominc.com), [sales01@ocomtech.com.cn](mailto:sales01@ocomtech.com.cn)

**Skype:** ocomsales01; **MSN:** ocomsales01@hotmail.com

**Ali TM:** cn1001868228; **QQ:** 1483705401

**Mobile/Wechat/Whatsapp:** 0086.189 4871 3992



Reliable One-Stop Supplier for POS and Auto-ID Related Products