Handheld Laser Barcode Scanner

(Model No.: OCBS-L009)

FEATURE:



- n 200scan/sec high scan rate and long reading distance;
- n Excellent decode capability;
- n KBW, RS232 and USB supported;
- $n\;$ Durable construction combined with future-proofing;
- n Grey and black color for option;

SPECIFICATION:

Performance Characteristics	
Light Source:	650nm visible
Scan Rate:	200 scans per second
CPU	32 bit
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Width of Scan	50mm@60mm, 220mm@200mm
Scanner Type:	Bi-directional
Operation mode	triggered
Resolution:	3mil high resolution series / 5mil long depth field series
Print Contrast	30%, minimum reflective difference
Minimum:	
Decode Capability:	UPC/EAN, UPC/EAN with Supplemental, UCC/EAN 128, Code 39, Code 39 Full
	ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Coda bar, Interleaved
	2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of
	5[]MSI/Plessey[]UK/Plessey[]UCC/EAN 128[]Chinese code []GS1 Data Bar
	[RSS]series

Scanning Angle	$\pm 65^{\circ}(tilt); \pm 60^{\circ}(pitch); \pm 42^{\circ}(yaw)$	
Physical Characteristics		
Interfaces Supported:	PS2, RS232, USB	
Voltage:	5V DC±5%	
Current:	85 mA (Operating); 100 (Max)	
Indicator	Beeper, LED	
Material	ABS+PC	
Stand	Optional	
Dimensions:	156*68*83 mm (L*W*H)	
Weight:	235g	
Color:	Grey and black	
User Environment		
Operating	0 Degree C~45 Degree C	
Temperature:		
Storage Temperature:	-40 Degree C~60 Degree C	
Humidity:	5%-90% (non-condensing)	
Electrostatic Discharge:	Conforms to +/-15KV air discharge and +/-8KV of contact discharge	
Ambient Illumination	0 ~ 100,000 LUX	
Drop Specifications:	Withstands multiple 1.5m drops to concrete surface	
Laser classification	EN60825-1[]class 1	