

32 bit Auto Sense Handheld Laser Barcode Scanner With Stand (Model: OCBS-LA09)

Specification:

| | |
|-----------------------------|--|
| Performance Characteristics | |
| Light Source: | 650nm visible |
| Scan Rate: | 200 scans per second |
| CPU | 32 bit |
| Reading Distance | 2.5 ~600mm (100% UPC/EAN) |
| Width of Scan | 50mm@60mm, 220mm@200mm |
| Scanner Type: | Bi-directional |
| Operation mode | Auto Sense |
| Resolution: | 3mil high resolution series / 5mil long depth field series |
| Print Contrast Minimum: | 30%, minimum reflective difference |
| Decode Capability: | UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese code, GS1 DataBar (RSS)series |
| Scanning Angle | ±65°(tilt); ±60°(pitch); ±42°(yaw) |
| Physical Characteristics | |
| Interfaces Supported: | PS2, RS232, USB for option |
| Voltage: | 5V DC±5% |
| Current: | 85 mA (Operating); 100 (Max) |
| Indicator | Beeper, LED |
| Material | ABS+PC |
| Stand | With |
| Dimensions: | 156*68*83 mm (L*W*H) |
| Weight: | 235g |
| Color: | Grey or black |
| User Environment | |
| Operating Temperature: | 0°C~45°C |
| Storage Temperature: | -40°C~60°C |
| Humidity: | 5%-90% (non-condensing) |
| Electrostatic Discharge: | Conforms to +/-15KV air discharge and +/-8KV of contact discharge |
| Ambient Illumination | 0 ~ 100,000 LUX |
| Drop Specifications: | Withstands multiple 1.5m drops to concrete surface |
| Laser classification | EN60825-1, Class 1 |

Product Details:





Features

Simple but not easy

200scan/sec high scan rate and long reading distance;





Excellent decode capability;



KBW, RS232 and USB supported;



Durable construction combined with future-proofing





Competitive price for 32bit model



|| All-round show





Parameter

| Performance Characteristics | |
|-----------------------------|---|
| Light Source: | 650nm visible |
| Scan Rate: | 200 scans per second |
| CPU | 32 bit |
| Reading Distance | 2.5 ~600mm (100% UPC/EAN) |
| Width of Scan | 50mm@60mm, 220mm@200mm |
| Scanner Type: | Bi-directional |
| Operation mode | Auto Sense |
| Resolution: | 3mil high resolution series / 5mil long depth field series |
| Print Contrast Minimum: | 30%, minimum reflective difference |
| Decode Capability: | UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar |

| | |
|---------------------------------|---|
| | Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, chinese code , GS1 DataBar (RSS) series |
| Scanning Angle | ±65°(tilt); ±60°(pitch); ±42°(yaw) |
| Physical Characteristics | |
| Interfaces Supported: | PS2, RS232, USB |
| Voltage: | 5V DC±5% |
| Current: | 85 mA (Operating); 100 (Max) |
| Indicator | Beeper, LED |
| Material | ABS+PC |
| Stand | Optional |
| Dimensions: | 156*68*83 mm (L*W*H) |
| Weight: | 235g |
| Color: | Grey and black |
| User Environment | |
| Operating Temperature: | 0°C~45°C |
| Storage Temperature: | -40°C~60°C |
| Humidity: | 5%-90% (non-condensing) |
| Electrostatic Discharge: | Conforms to +/-15KV air discharge and +/-8KV of contact discharge |
| Ambient Illumination | 0 ~ 100,000 LUX |
| Drop Specifications: | Withstands multiple 1.5m drops to concrete surface |
| Laser classification | EN60825-1, class 1 |

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which

3. INTERNATIONAL AIR MAIL, usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.





Monica Fu



OCOM Technologies Limited

Add: 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Tel: 0086.755.8605.3207 ext 801

Fax: 0086.755.8605.3207 ext 868

Web: www.ocominc.com

E-mail: sales01@ocominc.com, sales01@ocomtech.com.cn

Skype: ocomsales01; **MSN:** ocomsales01@hotmail.com

Ali TM: cn1001868228; **QQ:** 1483705401

Mobile/Wechat/Whatsapp: 0086.189 4871 3992



Reliable One-Stop Supplier for POS and Auto-ID Related Products