

# OCBS-T103 Cheap omni usb c# barcode scanner machine

(Model: OCBS -T103)

## Product Description

feature:

- High performance 32-bit hardware decoding;
- 20 scan lines in five directions;
- Multi-line/single line scanning function
- Scan window supports adjustment angle
- Support for various types of suffix settings

## specification:

|                           |                                                                                                                                       |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Performance parameter     |                                                                                                                                       |
| light source              | 650 nm visible laser diode laser                                                                                                      |
| system interface          | KBW, RS232, USB                                                                                                                       |
| Physical parameter        |                                                                                                                                       |
| Volume (Lx W x H)         | Without bracket: 140mm * 83mm * 75 mm<br>With stand: 157 mm * 98.3 mm * 100 mm                                                        |
| weight                    | Net weight (282 g); with stand (379 g)                                                                                                |
| support                   | Fixed mounting bracket                                                                                                                |
| colour                    | black                                                                                                                                 |
| Electrical parameters     |                                                                                                                                       |
| Input voltage             | 5.0 VDC +/- 10%                                                                                                                       |
| Rated current             | 275 mAh                                                                                                                               |
| power                     | 2W                                                                                                                                    |
| Laser class               | CDRH Class IIa; IEC 60825-1: Class I                                                                                                  |
| Environmental parameters  |                                                                                                                                       |
| Operating temperature     | 0°C - 40°C                                                                                                                            |
| Storage temperature       | -40°C -70°C                                                                                                                           |
| humidity                  | Relative humidity 5% to 95% (no condensation)                                                                                         |
| Antiknock characteristics | Withstand a drop of 1.2 meters.                                                                                                       |
| Lightfastness             | Indoor lighting, sunlight, fluorescent, incandescent, mercury, sodium vapor: 450 Ft candles (4844 Lux)<br>Daylight: 8000Ft (86111Lux) |
| Scanning parameter        |                                                                                                                                       |
| Scan mode                 | Omnidirectional 20 lines, 5 directions, 20 scanning lines                                                                             |
| Scanning speed            | 1500 times per second                                                                                                                 |
| Scanning angle            | 0~360 degrees (all round)                                                                                                             |
| Scan deviation            | +/- 50 degrees                                                                                                                        |
| Print contrast            | Minimum 25% reflection difference                                                                                                     |

|                     |                                                                                                                                                                          |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Scan depth          | 0~216mm @ 13mil (100%UPC / EAN)                                                                                                                                          |
| Rated working range | 5mil: (38%) 10~64mm<br>7.8mil: (60%) 0~152mm<br>10.4mil: (80%) 0~190mm<br>13mil: (100%) 0~216mm                                                                          |
| Lowest resolution   | 5mil                                                                                                                                                                     |
| Decoding ability    | UPC / EAN / JAN, UCC / EAN 128, Code128, Code 39, Code 39 Trioptic, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code 93, Code 11, Code bar, MSI, and the like. |

## ► Picture Show





OCBS-T103





OCBS-T103





OCBS-T103





OCBS-T103



## ► Company



## ► Certificates



## ► Payment



## ► Contact us

Richard Hu



## OCOM Technologies Limited

---

**Add:** 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

**Tel:** 0086.755.8605.3207 ext 808

**Fax:** 0086.755.8605.3207 ext 868

**Web:** [www.ocominc.com](http://www.ocominc.com)

**E-mail:** [richard@ocominc.com](mailto:richard@ocominc.com), [richard@ocomtech.com.cn](mailto:richard@ocomtech.com.cn)

**Skype:** ocominc2000; **MSN:** ocomtech@hotmail.com

**Ali TM:** szocominc; **QQ:** 2485890637

**Mobile/Wechat/Whatsapp:** 0086. 133 5293 2860



Reliable One-Stop Supplier for POS and Auto-ID Related Products