

# Image 2D Omnidirectional Barcode Scanner

(M/N:OCBS-T210)

<b>Performance Parameters</b>	
Light Source	Illumination 650nm LED
Optical Resolution	1280*720
Print contrast Signal	25% minimum reflective difference
Field of View:	45° (H) x 35° (V)
Roll/Pitch/Yaw	360° / ± 65° / ± 60°
Motion Tolerance	Up to 600cm per second(theoretical value)
Indicator	Blue LED & beeper
Interface	USB OR RS232
Symbologies: 2D	PDF417, MicroPDF417,Data Matrix, Maxicode,QR Code,MicroQR,Aztec
Symbologies: 1D	UPC/EAN, Code 128, Code 39, Code 39 , Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Industrial 2of 5, Martrix 2 of 5, Codabar, MSI/Plessy, GS1 Databar
<b>Electrical Parameters</b>	
Input Voltage	5V DC ±5%
Current - Standby	90mA
Current - Operating	400mA
<b>Mechanical Parameters</b>	
Case Material:	104mm×(L)96mm(W)×166mm(H)
Dimension:	300g (without package); 530g (Include package and accessories)
Weight:	ABS
Cable:	USB: HID KEYBOARD(default mode)
<b>Environmental Parameters</b>	
Operating Temperature	32° to 122° F / 0° to 50° C
Storage Temperature:	-40° to 158° F / -40° to 70° C
Humidity:	5% to 95%, non-condensing
Drop/Shock Specifications	Withstands 10Gs 0.06" double amp
Ambient Light Immunity	Immune to indoor lighting up to 1600 Lux. Immune to sunlight up to 86,000 Lux.



OCBS-T210





OCBS-T210

