

China shenzhen oem best hand free pos android auto-sense omni
wired 1d 2d qr code barcode reader manufacturer

(M/N:OCBS-T215)

Features:



Large reading window;

Quickly identify the screen 1D/2D code;

Hidden anti-pull data cable socket.

Specification

General	
Model	OCBS-T215
Interface	USB
Operating Voltage	5V
Starting Current	420mA
Work Current	400mA
Standby Current	270mA
Performance	
Sensor	Overall exposure 640*480 CMOS sensor
Light source	Red LED
Field view	57.2° (H), 44.2°(V)
Motion tolerance	> 0.3m/s
Scan Angle	Pitch ±70°@ 0°Roll and 0° Skew Roll 360°@ 0°Pitch and 0° Skew Skew ±70°@ 0°Roll and 0° Pitch
Symbol Contrast	20% minimum reflective difference
Ambient Light Immunity	0-100,000 Lux
Typical Depth of Field	Code39(5mil):20mm-80mm, EAN13(13mil):10mm-160mm QR(15mil):10mm-140mm Data Matrix (15mil):10mm-100mm PDF417 (10mil):10mm-120mm
Decoding ability	(Codabar),(Code 39),(Code 32),(Industrial 2 of 5),(Interleaved 2 of 5),(Standard 2 of 5),(Matrix 2 of 5),(Code 93),(Code 11),(Code 128),(UPC-A),(UPC-E),(EAN/JAN-8),(EAN/JAN-13),(GS1 DataBar(RSS14) (PDF417),(QR Code),(Micro QR),(Data Matrix),(Aztec),(Hanxi code)
Physical	
Weight	Gross:640g
Package	230*170*95mm
Environment	
Working temperature& humidity	0 to 45 degrees centigrade , 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation















Model: OCBS-T215

Interface: USB



OCBST2152214100001

Made in China





1. Introduction	1
2. Safety Precautions	2
3. Installation	3
4. Operation	4
5. Troubleshooting	5
6. Appendix	6

Special Precautions Manual

1. The device and also its charging circuit are not to be used in the presence of flammable or explosive gases or vapors. When charging, avoid or prevent contact with water or other liquids.

2. The device shall not be exposed to a direct flame, and a small amount of petrol or oil may be added to the device, and then exposed only with caution.

3. Special Precautions: This instrument has been strictly and carefully checked and controlled, but it will have to verify the instruments and circuit or splicing lead techniques used, whenever good devices will be connected in the same manner of the instruction without remove the copyright of this technology is subject to the company, and no other work or technology may modify it.

THE POWER SUPPLY UNIT



1. The device is not to be used in the presence of flammable or explosive gases or vapors. When charging, avoid or prevent contact with water or other liquids.

2. The device shall not be exposed to a direct flame, and a small amount of petrol or oil may be added to the device, and then exposed only with caution.

3. Special Precautions: This instrument has been strictly and carefully checked and controlled, but it will have to verify the instruments and circuit or splicing lead techniques used, whenever good devices will be connected in the same manner of the instruction without remove the copyright of this technology is subject to the company, and no other work or technology may modify it.





2D Barcode Scanner
Model: OCBS-T215 Color: Black
Interface: USB CE FC
Power Input: 5V1A
OCBS T215 2214100001
Made in China