

8-inch Windows Rugged Tablet

(Model no.: OCBS-T802W)

Specification

Model	OCBS-T802W
Material	PC+TPU
Color	Black
Display	8-inch TFT colorful screen
Resolution	1200*1920
Touch Panel	5 points tempered glass capacitive screen G+G
Camera	Front-facing camera: 5MP, Rear 8MP, autofocus with flash
Buttons	Power *1, Volume + *1, Volume - *1 F Key *1 (Barcode Scanning), When there is no scanning function, it can be customized, Home Key*1
Speaker	8Ω/1W Speaker *2
OS	Windows 10 Home Optional: Windows 10 Pro, Windows 10 IOT
Performance	
Motherboard	Intel JASPER LAKE N5100 processor, 4-core, Maximum frequency 2.8GHz
GPU	Intel® HD Graphics Gen 11 LP
Storage	RAM 8GB DDR, ROM 128GB eMMC
Battery	Removable Li-polyment Battery, 5000mAh/7.6V
WIFI	WIFI 802.11(a/b/g/n/ac) Dual frequency 2.4G+5.8G WIFI
Bluetooth	BT5.0 (BLE) class1 Transmitted distance:10m
Indicator Light	Blue indicator *1 (Blue light is always on when the machine is turned on, and off when the machine is turned off) R&G two-color lamp *1 (Low power red flickers, red is always on when charging, green is always on when full)
I/O Interface	USB3.0 *1, Type C 3.1 *1, 3.5mm Standard ear jack *1, HDMI 2.0a mini *1 3 in1 card holder (Micro SD card, up to 512GB; Nano SIM *1) 12PIN Pogo Pin *1 (Charging interface, USB signal connection base)
Optional functions	QR Code Scanner(Honeywell N3680) NFC: NXP300 NXP NFC 13.56MHz Supports 14,443A/14,443B/15,693/18,092/mobile protocol under ISO/IEC. Card reading distance: 4cm
4G	Eurasian: LTE FDD: B1/B3/B5/B7/B8/B20 LTE-TDD: B40 WCDMA: B1/B5/B8 GSM: 900/1800 Optional:EC25-AF, 750-VA, 750-VSA
GPS	Support GPS (L1 1.575GHz C/A code), GLONASS (L1 1.602GHz), Cold start time is not more than 60s

Physical Specifications	
Dimension	236.7*155.7*20 mm
Weight	910g
Package box	323*173*62mm/1.38kg
10 in 1 carton	630*338*206mm/16.9kg
Environmental Specifications	
Operation Temperature	-20 °C to 60 °C
Storage Temperature	-30 °C to 70 °C
Humidity	95% Non-Condensing
Drop Specifications	MIL-STD-810G: 1.22m drop
ESD	± 8kV contact discharge, ± 15kV air discharge
Accessories	
Adapter	AC100V ~ 240V 50Hz/60Hz, Output TYPE-C, 12V 4A













