

Features:

- 200MM/S Scan Speed
- 10-60cm long depth of field
- 70 m long Distance 2.4G Wireless transmission
- Compatible with multiple language layouts
- 1.5m free fall on concrete surface
- 1500mAh lithium-ion battery

Specification:

General Information	
Model	OCBS-W013
Color	white,black
Material	ABS+PVC+PC
IP Grade	IP52
Processor	32-bit MCU
Button Life	>100000
Interface	USB cable;Wireless 2.4G transmission
Language Supported	English(Customizable language)
Power Supply	5V ±5% ,Built-in 3.7v 1500mAh lithium-ion battery
Operating current	50MA(operating mode); 30MA(standby mode)100MA(maximum peak)
Prompt Mode	Buzzer, Indicator Light(LED)
Trigger Mode	Manual ;Continuous scanning
Memory	64K(About 3500 14bit 1D barcodes)(the memory capacity can be customized)
Working time	about 24 hours
Charging time	6-7 hours
ESD Protection	15KV air discharge
Shock Resistance	1.5m free fall on concrete surface
System Supported	Linux,Android,Windows XP,7,8,10,MAC
Scanning Performance	
Light source	Visible laser diode, wave length 650nm
Scanning speed	200 scans/sec
Scanning Distance	10mm-600mm
Print Contrast	35%
Resolution	4mil
Transmission Distance	70m
Reading Mode	laser
Scanning Angel	Roll35°;Pitch65°;Yew65°
Scanning Depth	Code39 5mil:3cm - 8cm Code39 10mil:4cm - 45cm
Bit Error Rate	1/5000000
Decoding ability	Code25-Interleaved Code25-Standard Code25-Matrix Code39-Regular Code39-FullASCII Code32 Code93-Regular Code93-FullASCII Code128
Physical Characteristics	
Weight	Gross:300g
Package	183*118*85mm
20 in 1 carton	460*400*270mm/7.05kg
Environment	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation









