

High Performance 1D/2D Wireless Barcode Scanner with Cradle

(Model No.: OCBS-W236)

Feature:

Subvert traditional design, with simple assembly stand;
0.3 million overall situation exposure, 60fps fast speed;
3mil resolution bar code reading ability;
Support reading many kinds of 1D&2D bar code;
Support 2.4G wireless and Bluetooth communication;
2.4G high power receiver, the farthest transmission distance can reach 150m;
2200mAh high capacity battery;
Can store 40,000 EAN13 bar codes;
Support reading difficult bar codes (blurred, wrinkled, fuzzy, low contrast, high density, etc.);
Widely used in different host systems, such as windows 7/8/10, iOS, Android and Linux system, etc.;
Most of application at retail stores, supermarket, chains, medical, luxury, clothing, jewelry, tobacco, etc..

Specification:

Performance parameters	Model	OCBS-W236
	Image Sensor	CMOS
	Light Source	White LED(lighting) red LED aiming
	CPU	32bit ARM
	COMS Image Size	640x480
	Exposure	overall situation exposure
	Scanning speed	60fps
	Resolution	≥3mil
	Decoding Depth	60-360mm
	Scan Angle	Rotate 360°, inclination 65°, elevation 60°
	Scanning mode	Manual trigger/automatic induction
	Battery	2200mAh
	Wireless method	150meter 2.4G and 10meter Bluetooth
	Storage capacity	40000 pieces EAN-13 code
	Decoding ability	1D: Codabar□Code11□Code39□Code32□Interleaved 2 of 5□Industrial 2 of 5□Matrix 2 of 5□Code93□Code128□GS1-128□UPC-A□UPC-E□EAN 8□EAN 13□GS1 DataBar□RSS14□□GS1 DataBar Limited□GS1 DataBar Expanded□etc 2D: PDF417□Micro PDF417□QR Code□Micro QR□Data Matrix□Aztec Code
Other parameters	Size	L*W*H= 163*68*80(mm)
	Weight	185g
	Material	ABS+TPU
	Input voltage	DC 3.6V-5.5V
	Working current	142mah
	Standby current	42mah
	Prompt	Beep&LED
	Interface	USB-HID
	Cable standard	1.6m
	Working temperature	0℃□50℃
	Working humidity	Relative humidity 5%-95%(no condensation)
	Storage temperature	-40℃□70℃
	Anti-ambient light	0□5000Lux(fluorescent)□0□100,000Lux(Sunlight)



OCBS-W236





OCBS-W236

