

## Features:

Ergonomic design, comfortable using

Read all mainstream 1D 2D barcodes in the market easily (4mil)

Interface: USB, bluetooth 4.2, Wireless 2.4G

Ultra-low power consumption, continuous working time 20h

Bluetooth and bluetooth long wireless distance could be more than 60 m, can be used in mobile phone and PC

Widely used in supermarket, warehouse, mobile payment, chain stores

## Specification:

Model	OCBS-W238
Power Supply	DC 5V@250mA(work)
Interface Type	Type-B
Communication Mode	USB Wireless 2.4G Wireless Bluetooth 4.2
Receiver	Used to receive and transmit scanner data.
Cable	USB, connect the scanner to a host device and charging.
Drop Height	1.5m
Temp. Test	30 minutes for high Temp., 30 minutes for low Temp., (High Temp. 60°C, Low Temp. -20°C)
Scan Type	CMOS
Pixel	1.3M CMOS Global exposure
Resolution	100CM/S
Depth of field	50mm~900mm
Scan Mode	Trigger mode Auto sense mode
Scan angle	Roll $\pm 360^\circ$ Pitch $\pm 60^\circ$ or greater Yaw $\pm 55^\circ$ or greater
Visual angle	Horizontal 40° x Vertical 30°
Print Contrast Signal	$\geq 25\%$ PCS
Wireless transmission distance	2.4GHz, 70meters; Bluetooth 30meters Open distance
Storage	350KB over 20,000 Product code
Battery capacity	5000mAh
Battery charging time	About 7 hours
Continuous working time	$\geq 36$ hours
Standby time	1 month
Decoding ability	1D: UPC-A, UPC-E, EAN-8, EAN-13, Code 128, GS1-128, Code 39, Code 32, Code 93, Code 11, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5 (Straight 2 of 5), Codabar (NW-7, GS1 databar) 2D: QR Code, Micro QR Code, Data Matrix, PDF417, Micro PDF 417, Aztec, etc.
Weight	Gross: 710g
Package	230*130*132mm
20 in 1 carton	680*470*280mm/15kg
<b>Environment</b>	
Working temperature & humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature & humidity	-20 to 60 degrees centigrade, 10%~90% No condensation









