

Thermal Barcode Label Printer

(Model No.: OCBP-005)

Features:

- l Label paper auto position;
- l Labels peel off automatically;
- l Adjust the printer head pressure;
- l Compatible with plenty of label software;
- l BMP, PCX, BAC images download store;
- l Support Serial, USB, LAN together;
- l Support PDF417, QR CODE, DOTMATRIX;



Specifications:

Printer Model	OCBP-005
Resolution	203 DPI (8 dot/mm)
Printing Method	Direct Thermal

Printing head temperature sensor	Thermal sensitive resistance
Printing head position sensor	Micro switch
Paper exists detection	Photoelectric sensor
Printing Speed	127 mm / sec (max); 50.8mm/sec (min)
Printing Width	16 mm ~ 76 mm
Media	Media Type: Paper roll, sticker, label fold, etc. Media diameter: Inner dia:25mm; Outer dia: 80mm
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts
Enlargement & rotation	1 to 10 times enlargement in both directions; 0 Degree , 90 Degree, 180 Degree, 270 Degree, 360 Degree rotation
Paper off type	Tear off & peel off
Memory	2MB Flash Rom, 2MB DRAM
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM
Barcode	CODE128, EAN128, ITF, Code39, Code93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPC-E, UPCE+2, UPCE+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14, PDF417, QR CODE, DATMATRIX
Interface	USB + RS232 + LAN or USB
Power	Input: 24VDC, 2.5A
Environment	Operating Temperature: 5 Degree C to 45 Degree C Storage Temperature: -40 Degree C to 55 Degree C Operating Humidity: 20% ~ 80%, non-condensing, Free air Storage Humidity: <=93%(40 Degree C), non-condensing, Free air
Dimension	Size: D220mm * H148mm *W150mm