

OCOM POS-B11.6 Restaurant System All In One Touch Screen POS Desktop Computer Device

(M/N:POS-B11.6/B11.6-A)

Features:

- Elegant B base for pos machine.
- Intel Celeron Processor J1900 Quad core 2.0GHz High Configuration CPU for Windows system
- 2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system
- 2GB RAM+8GB ROM standard (Android)
- 2GB RAM+32GB SSD standard (Windows)
- 11.6 inches Multi-point capacitive touch screen
- 11.6 inches non-touch second screen,
- Embedded 58mm or 80mm thermal printer(Optional)
- Embedded MSR RFID reader(Optional)
- Stylish display panel

Applications:

- Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Picture show:



Parameter:

| | |
|--------------------------|---|
| Model | POS-B11.6/POS-B11.6-A |
| Main Board□ | Intel Celeron Processor J1900 Quad core 2.0GHz (Windows) |
| Main Board□ | 2.0GHz A83T ARM 8-Core Cortex-A7 Processor (Android) |
| OS□ | Windows7(Beta) |
| OS□ | Android 5.1 |
| Memory□ | 2GB RAM 32GB SSD (Windows) |
| Memory□ | 2GB RAM 8GB ROM (Android) |
| Touch Screen | Multi-point capacitive touch |
| Screen Size | 11.6 inch,16:9 |
| Customer Display | LCD customer display (Default), Options: 11.6inches non-touch screen, VFD customer display, Other size Scree, or non-customer display |
| Color | Black or White |
| Printer | 58mm big gear thermal printer or 80mm thermal printer with Auto cutter (Options) |
| I/O port□□J1900□ | USB*4 |
| | RJ45*1 |
| | RJ11*1□optional□ |
| | VGA*1 |
| | DB9 RS232 port *1,(can add 2 ports for optional) |
| I/O port(□A83T) | RJ11*1 (Opional) |
| | TF slot *1 |
| | RJ45*1 |
| | USB*2 (can add 4 ports for optional) |
| | DB9 RS232 port*1 |
| | Audio*1 |
| | USB OTG port*1 |
| Operating temperature | 0°C to 40°C |
| Other Function (Android) | Bluetooth, WIFI |
| Optional items(Windows) | RFID,MSR camera,3G, DB25 parallel port, DB9 RS232 port*3 |
| Optional items(Android) | 3G,4G camera, LCD VFD display,RFID,MSR,Other size Screen |
| Storage temperature | -20°Cto 60°C |
| Packing dimension | 46*43*51cm |
| Power adapter | 110-240V/50-60HZ AC power Input, 12/24V output depending on the printer |