

OCPD-LCD500 5 " color panel POS small lcd display with stand

(M/N:OCPD-LCD500)

Features:

Support OPOS driver;

Compatible with 15 kinds command,like ESC/POS,CD5220 and so on;

Compatible with 20 countries Languages,other languages can be customized;

Provide custom setup software all customizations can be done by the end user;

Support setting booting image;

Three display areas can setting background color and character color;

Top display area can setting logo and fixed characters;

The middle display area can be switched to 2*20 characters or 4*20 characters display;

The bottom display area supports custom scrolling play characters.

Data sheet:

General	Display Method	TFT - LCD Display 5 inch COLOR PANEL
	Number of characters	40 character(20columns×2line)/ 80 character(20columns×4 line)
	Brightness	350cd/m ²
	Resolution	480*272 or 800*480
	Character font	24*48/40*80 dot matrix
	Character type	95 Alphanumeric 32 international characters
	Character size	8H×5.25Wmm
	Dot size X×Y	0.23×0.23mm
	Panel Dimension	113.5Lmm×65.5Wmm×40Hmm
	Pole Dimension	Per support length 163L×27.65DIAmm/ 80L×27.65DIAmm
	Base Dimension	126L×89W×13.5Hmm
	Viewing Angle	Max.135°
	Horizontal Rotation	Max.355°
	Weight	490 grams/506grams
Commands Mode	15 kinds, E.g LD220, ESC/POS, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL etc	
Language Support	CP437, Katakana, CP850, CP860, CP863,CP865, WCP1252, CP857, WCP1250, WCP1253,WCP1255, WCP1251, CP866, CP852, CP737, CP858, CP864,WCP1257, WCP1258TaiCP874	

Interface		RS-232 serial/USB
Connection	Baud	Direct connection 9600/19200/38400/57600/115200 bps
Reliability	MTBF	30000 hours
Power	Consumption	5-24 VDC
Safety	EMC standards Safety standards	FCC CE ROHS





OCPD-LCD500





OCPD-LCD500





OCPD-LCD500





OCPD-LCD500

