

OCP-585 2 inch lottery machine printer

Specification:

| | |
|------------------------|---|
| Printing Method | Direct thermal |
| Print Density | 384dots/line (203DPI) |
| Character Size | 384dots/line, ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm |
| Barcode Type | JAN13□EAN13□JAN8□EAN8□CODE39 QR □optional□ |
| Printing Command | Compatible with PSON ESC/POS |
| Language | Buyer language support |
| Printing Speed | 90mm/sec |
| Paper Width | 57.5±0.5mm |
| Paper Thickness | 0.06-0.08mm |
| MCBF(life) | 50km |
| Dimension | 190*132*119mm |
| Gross Weight | 1.2KG |
| Auto Cutter | manual cutter |
| Sensor | Paper Near End Sensor, Paper End Sensor, Cover open sensor |
| Roll Paper | Φ75mm |
| Interface | RS-232C, Parallel, USB, LAN |
| Driver | Win 9X, Win 2000, Win 2003, Win XP, Win Vista, Win 7 compatible with ESPON |
| Adapter Voltage Input | AC 110V/220V, 50-60Hz |
| Adapter Voltage Output | DC12V/3A |
| Printer Input Voltage | DC12V/3A |
| Cash Drawer Control | DC12V/1A |
| Working Temperature | 0-45°C, Humidity: 10-80% |
| Saving Temperature | -10-60°C, Humidity: 10-90% |
| Certificate | CE/FCC/CCC/RoHS |

Product Details:



Relevant documents:

- [*Specification](#)
- [*Program Manual](#)
- [*Instruction Manual](#)
- [*Driver for WinXP Win2000 WinVista Win7 Win8-32bit](#)
- [*Driver for Win7and Win8-64bit](#)
- [*Driver for Linux](#)

[*Printer Parameters Setting Tools](#)

[*USB Printdemo\(Application Software demo\)](#)

[*SDK for Android](#)

[*CD Files](#)