

58MM Thermal Printer

(M/N:OCP-586)

Features:

- l. Elegant and compact design
- m. Fast, reliable and versatile thermal receipt printer
- n. Widely applied in retail, catering, hospital, bank, etc
- o. Triple connection interface as well as its simple installation kit
- p. Compatible with ESC/POS
- q. Printing head life: 50KM

Specification

General	
Model	OCP-586
Name	58mm desktop thermal printer
Color	Black or white
Interface	RS-232, Parallel, USB, Lan and bluetooth (optional)
Power supply	Input AC 100V-240V,50-60Hz,Output DC 12V/3A
Cash drawer	DC 12V/1A
Printer head lifespan	50KM
Cutter	Manually cutting
Sensors	Paper End , Cover Open
Accessories	Data cable,power adaptor,power cord,paper roller,CD,manual
OS supporting	Compatible with windows,Linux,Adroid,IOS
Safety standards	CE ,FCC,Rohs etc
Printing capability	
Printing method	Direct thermal line
Resoluiton	203 DPI(dot per inch)
Printing speed	90mm/s
Print width	48mm
Printing Command	Compatible with ESC/POS
Barcode and character	
Barcode	JAN13(EAN13)JAN8(EAN8)CODE39 QR (Optional)
Character size	384dots/line, ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Character set	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe Greek/Hebrew/East urope/Iran/WPC1252/PC866/PC852 PC858/IranII/Latvian/ Arabic/PT151,1251/PC747 WPC1257/Vietnam/PC864/Hebrew/WPC1255/Thai
Media	
Paper type	thermal roll paper
Paper width	57.5±0.5mm
Paper roll diameter	50mm Max

Paper thickness	0.06-0.08mm		
Physical			
Dimension	190*132*119 mm		
Weight	1.2kg		
Package box	210*210*150 mm		
12 in 1 carton	630*430*320mm/15kg		
Environment			
Working temperature& humidity	0 to 45 degrees centigrade,	10%~80%	No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade ,	10%~90%	No condensation

Product details









