

58mm Thermal Receipt Printer With 83mm Big Paper Holder

(M/N:OCP-587)

Product description:

OCP-587 is a Mini 58MM thermal printer, the design exquisite fashion, small and smart, with highly technological sense. Using large motor and a big gear movement design, drag 83MM large diameter roll and achieve 130 mm / s high speed printing at the same time, the perfect solution to solve the problem of common 58mm printer support small diameter roll, print speed slow, enable print more efficient. At the same time, provides a rich interface, including network port (100M), WIFI, Bluetooth, GPRS, enable print more flexible and convenient.

Product performance:

- Appearance compact design, fashion technology;
- Easy paper feed structure, simple and convenient operation;
- High reliability of large motor and large gear movement;
- 130mm / s speed print, significantly improve the printing efficiency;
- Big paper warehouse design, the perfect support for 83MM large diameter rolls;
- Rich interface optional: USB, COM, Internet (100M), WIFI, Bluetooth, GPRS;
- Support GB18030 large font and multi language ;
- Supports LOGO and graphics downloads and print;
- Supports Windows, Linux, Android and IOS system print;
- 100M Ethernet interface, print quickly while avoiding losing bills.

Printer Parameters:

| Items | Parameters | |
|--------------------------|------------------------|--|
| Print parameters | Printing Method | Thermal Line |
| | Printing Method | 48MM |
| | Resolution | 384dots/Line/8dots/mm[203dpi] |
| | Printing Speed | 130mm/Second |
| | Interface | USB/COM/Internet/100M/WIFI/GPRS/Bluetooth |
| | Line Spacing | 3.75 mm[Can adjust line spacing by command] |
| | Line No. | Font A:32 character/Line Font B:42 character/Line Simple traditional Chinese-16 lines |
| | Character | Standard GB18030 simplified / traditional Chinese Fonts |
| | Character Size | ANK character[Font A]1.5×3.0mm[12×24] Font B]1.1×2.1mm[9×17] Simplified/traditional Chinese[3.0×3.0mm[24×24 Dots]] |
| | Extended character set | PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/Iran/Latvian/Arabic/PT151.1251/PC737/WPC1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151.1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai) |
| Graphics printing | Bar code | 1D bar code[UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128 2D bar code[QR CODE Supports bitmap download and print |
| | Printing Type | Thermal Roll |
| | Paper | Width 57.5±0.5mm Diameter ≤83mm Feed Method Easy feed(Clameshell feed) |
| Print commands | Commands | ESC/POS |
| | Power | Input[AC 100V-240V,50-60Hz Output[DC 12V/2A Casher Drawer output DC 12V/1A |
| Buffer | Input Buffer | 4K |
| | NV Flash | 40K |
| physical characteristics | Weight | 750g |
| | Dimension | 180*115*127(MM) |
| Environment | Working Temp | [5 ~ 45°C] Humidity[10 ~ 80% |
| | Storage | Temp[-10 ~ 50°C] Humidity[10 ~ 90%[No dew] |
| Reliability parameter | Print Head Life | 100KM[print density≤12.5] |
| Software | Driver | Android,IOS, Linux, WinXP, Win7, Win8, Win8.1, Win10 |

Application:

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal



Relevant documents:

[Driver and CD files](#)