58mm barcode printing thermal receipt paper printer with inner power adaptor

(OCPP-58E)



Product Introduction:

OCPP-58E is a well-designed economic printer for common thermal bill printing ,this mold is with solid material, Exquisite workmanship. Transparent cover design, simple and fashion, easy for users to know the paper rolls' Using status, OCPP-58E adopt built-in power supply, not only can save space, but also easy for users to configure and use the printers. It's a very good choice for economical printing.

Product Features

- •Simple and fashion, With solid material, exquisite workmanship.
- Easy paper install structure, simple and convenient to operate
- Built-in power supply design, to save space and more convenient to configure;
- ●Transparent cover design, the user can know the paper roll's using status anytime;
- •Support GB18030 big font, easy to print uncommon characters
- Support multi language print, suitable for users all over the world;
- Support download and print LOGO&graphics;
- Support Windows, Linux, Android and IOS system printing

Application Area☐

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

Parameters

| Items | Parameters |
|-------|------------|

| | Printing Method | Thermal Line |
|---------------------|------------------------|---|
| Print parameters | Printing Width | 48MM |
| | Resolution | 384dots/Line∏8dots/mm∏203dpi∏ |
| | Printing Speed | 90mm/Second |
| | Interface Type | USB∏USB+Bluetooth |
| | Line Spacing | 3.75 mm∏Can adjust line spacing by command∏ |
| | Line No. | Font A:32 character /Line |
| | Line No. | Font B:42 character/Line |
| | | Simple,traditional Chinese-16 lines |
| | Character | Standard GB18030 simplified / traditional Chinese Fonts |
| | Character Size | ANKcharacter∏Font A∏1.5×3.0mm∏12×24dots∏ |
| | Character Size | Font B∏1.1×2.1mm∏9×17dots∏ Simplified/Traditional |
| | | Chinese∏3.0×3.0mm(24×24 dots∏ |
| Bar code | Extended character set | PC437/Katakana/PC850/PC860/PC863/PC865 |
| Character | | PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/ |
| | | Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/ |
| | | Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/ |
| | | PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/ |
| | | (Vietnam)/(Thai) |
| | Bar code | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ |
| | | CODABAR/CODE93/CODE128 |
| Graphics | Graphics printing | Supports bitmap download and print |
| printing | | |
| Paper | Туре | Thermal Roll |
| | Width | 57.5±0.5mm |
| | Diameter | ≤60mm |
| | Feed Method | Easy feed(Clameshell feed) |
| Print | Commands | ESC/POS |
| commands | | |
| Power | Power Adaptor | Input AC 100V-240V,50-60Hz |
| | | Output DC 12V/2A |
| | Casher Drawer output | DC 12V/1A |
| Buffer | Input Buffer | 4K |
| | NV Flash | 40K |
| physical | Weight | 590g |
| characteristics | Dimension | 185*130*112(MM) |
| Environment | Working | Temp[]5 ~ 45°C[] Humidity[]10 ~ 80% |
| | Storage | Temp[]-10 ~ 50°C []Humidity[]10 ~ 90%[]No dew[] |
| Reliability | Print Head Life | 50KM□print density≤12.5□ |
| parameter | | |





OCPP-58E











