

58mm Thermal Receipt Printer

(OCP-58E)

Parameters

Items	Parameters	
Print parameters	Printing Method	Thermal Line
	Printing Width	48MM
	Resolution	384dots/Line 8dots/mm 203dpi
	Printing Speed	90mm/Second
	Interface Type	USB USB+Bluetooth
	Line Spacing	3.75 mm Can adjust line spacing by command
	Line No.	Font A:32 character /Line Font B:42 character/Line Simple,traditional Chinese-16 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts
Bar code Character	Character Size	ANKcharacter Font A 1.5×3.0mm 12×24dots Font B 1.1×2.1mm 9×17dots Simplified/Traditional Chinese 3.0×3.0mm(24×24 dots)
	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/ EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/ 1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)(Vietnam)/(Thai)
Bar code	Bar code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128
	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤60mm
	Feed Method	Easy feed(Clameshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input AC 100V-240V,50-60Hz Output DC 12V/2A
	Casher Drawer output	DC 12V/1A
Buffer	Input Buffer	4K
	NV Flash	40K