Cheap 2 inch POS58 Thermal Printer Driver Download

(Model:OCPP-58E)



Product Introduction:

OCPP-58E is a well-designed economic printerfor common thermal bill printing ,this mold is with solid material, Exquisiteworkmanship. Transparent cover design, simple and fashion, easy for users toknow the paper rolls' Using status, OCPP-58E adopt built-in power supply, notonly can save space, but also easy for users to configure and use the printers. It's a very good choice for economical printing.

Product Features□

- •Simple and fashion, With solid material, exquisitework manship.
- Easy paper install structure, simple and convenient tooperate
- •Built-in power supply design, to save space and more convenient to configure;
- •Transparent cover design, the user can know the paperroll's using status anytime;
- •Support GB18030 big font, easy to print uncommoncharacters
- •Support multi language print, suitable for users all over the world;
- Support download and print LOGO&graphics;
- •Support Windows, Linux, Android and IOS system printing

Application Area□

Shoppingmalls, restaurants, stores, warehousing, taxation, banking, medical, postal

Parameters

in .		
Items		Parameters
Print		Thermal Line
		8MM
	Resolution	B84dots/Line[Bdots/mm[]203dpi[]
		90mm/Second
		USB[]USB+Bluetooth
		B.75 mm[Can adjust line spacing by command[]
	Line No.	Font A:32 character /Line
		Font B-42 character/Line
		Simple, traditional Chinese-16 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANKcharacter[]Font A[]1.5×3.0mm[]12×24dots[]
		Font $B[1.1\times2.1mm]9\times17dots[]$ Simplified/Traditional Chinese[]3.0 $\times3.0mm(24\times24\ dots[]$
Bar code	Extended	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)/(PC1001)
Character	character set	
	Bar code	UPC-A/UPC-E/[AN13(EAN13)/]AN8(EAN8)CODE39/ITF/
		CODABAR/CODE93/CODE128
Graphics	Graphics printing	Supports bitmap download and print
printing		
Paper	Туре	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤60mm
	Feed Method	Easy feed(Clameshell feed)
Print	Commands	ESC/POS
commands		
Power	Power Adaptor	Input[]AC 100V-240V,50-60Hz
		Output[TDC 12V/2A
	Casher Drawer	DC 12V/IA
	output	
Buffer	Input Buffer	AK
	NV Flash	HOK
physical	Weight	590q
characteristics	Dimension	I85*130*112(MM)
	Working	[Femp[5 ~ 45°C] Humidity[10 ~ 80%
	Storage	Temp[-10 ~ 50°C [Humidity- 10 ~ 90% No dew
	Print Head Life	50KM∏print density≤12.5∏
parameter		



