

OCPP-58E OCOM 58mm qr code restaurant bill receipt pos thermal printer

(OCPP-58E)

Product Introduction:

OCPP-58E is a well-designed economic printer for common thermal bill printing, this model is with solid material, Exquisite workmanship. Transparent cover design, simple and fashion, easy for users to know the paper rolls' Using status, OCPP-58E adopt built-in power supply, not only can save space, but also easy for users to configure and use the printers. It's a very good choice for economical printing.

Product Features

Simple and fashion, With solid material, exquisite workmanship.
Easy paper install structure, simple and convenient to operate
Built-in power supply design, to save space and more convenient to configure;
Transparent cover design, the user can know the paper roll's using status anytime;
Support GB18030 big font, easy to print uncommon characters
Support multi language print, suitable for users all over the world;
Support download and print LOGO & graphics;
Support Windows, Linux, Android and IOS system printing

Application Area

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

Parameters

Items		Parameters
Print parameters	Printing Method	Thermal Line
	Printing Width	48MM
	Resolution	384dots/Line 8dots/mm 203dpi
	Printing Speed	90mm/Second
	Interface Type	USB USB+Bluetooth
	Line Spacing	3.75 mm Can adjust line spacing by command
	Line No.	Font A:32 character/Line Font B:42 character/Line Simple, traditional Chinese-16 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤60mm
	Feed Method	Easy feed(Clameshell feed)
Print commands	Commands	ESC/POS

Power	Power Adaptor	Input□AC 100V-240V,50-60Hz Output□DC 12V/2A
	Casher Drawer output	DC 12V/1A
Buffer	Input Buffer	4K
	NV Flash	40K
physical characteristics	Weight	590g
	Dimension	185*130*112(MM)
Environment	Working	Temp□5 ~ 45°C□ Humidity□10 ~ 80%
	Storage	Temp□-10 ~ 50°C □Humidity□10 ~ 90%□No dew□
Reliability parameter	Print Head Life	50KM□print density≤12.5□