

58mm Thermal Receipt Printer

(OCPP-58E)



Product Introduction:

OCPP-58E is a well-designed economic printer for common thermal bill printing, this model is with solid material, Exquisite workmanship. Transparent cover design, simple and fashion, easy for users to know the paper rolls' Using status, OCPP-58E adopt built-in power supply, not only can save space, but also easy for users to configure and use the printers. It's a very good choice for economical printing.

Product Features

- Simple and fashion, With solid material, exquisite workmanship.
- Easy paper install structure, simple and convenient to operate
- Built-in power supply design, to save space and more convenient to configure;
- Transparent cover design, the user can know the paper roll's using status anytime;
- Support GB18030 big font, easy to print uncommon characters
- Support multi language print, suitable for users all over the world;
- Support download and print LOGO & graphics ;
- Support Windows, Linux, Android and IOS system printing

Application Area

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

Parameters

Items	Parameters
Print parameters	Printing Method Thermal Line
	Printing Width 48MM
Interface Type	Resolution 384 dots/Line [8 dots/mm] [203 dpi]
	Printing Speed 90mm/Second
Line Spacing	Interface Type USB [USB + Bluetooth]
	Line No. 3.75 mm [Can adjust line spacing by command]
Character	Font A: 32 character/Line
	Font B: 42 character/Line
Character Size	Simple, traditional Chinese - 16 lines
	Standard GB18030 simplified / traditional Chinese Fonts
Extended character set	Font A: [1.5 x 3.0mm] [12 x 24 dots]
	Font B: [1.1 x 2.1mm] [9 x 17 dots] Simplified/Traditional Chinese [3.0 x 3.0mm] [24 x 24 dots]
Bar code	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/Iran/Latvian/Arabic/PT151,1251/PC737/WPC1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/ITF/CODABAR/CODE93/CODE128
Graphics printing	Supports bitmap download and print
	Type
Paper	Width
	Diameter
Feed Method	Feed Method
	Commands
Power	Power Adaptor
	Input [AC 100V-240V, 50-60Hz]
Casher Drawer output	Output [DC 12V/2A]
	DC 12V/1A
Input Buffer	4K
	NV Flash
Weight	40K
	590g
Dimension	185*130*112 (MM)
	Temp [5 ~ 45°C] Humidity [10 ~ 80%]
Working	Temp [10 ~ 50°C] Humidity [10 ~ 90%] (No dew)
	Storage
Print Head Life	50KM [print density ≤ 12.5]
	Reliability parameter