

# 58MM Thermal Receipt Printer

(M/N:OCP-58E)

## Features:

1. Simple and fashion,with solid material,exquisite workmanship
2. Easy paper feed structure, simple and convenient operation
3. Built-in power supply design,saving much space and conveniently configure
4. Transparent cover make users easily know the paper roll status
5. Support GB18030 big font,easy to print uncommon characters
6. Support download print LOGO & graphics

## Specification

Model	OCP-58E
name	58mm desktop thermal printer
color	Black or white
interface	USB,USB+Bluetooth(1 to 1),USB+Bluetooth(1 to many)
Power supply	Input AC 100V-240V,50-60Hz,Output DC 12V/2A
Cash drawer	DC 12V/1A
Printer head lifespan	50KM print density≤12.5
cutter	Manually cutting
Buffer	Input buffer 4K,NV Flash 40K
Accessories	Data cable,power adaptor,power cord,paper roller,CD,manual
OS supporting	Compatible with windows,Linux,Adroid(IOS only for bluetooth printer)
Safety standards	CE ,FCC,Rohs etc
Printing method	Direct thermal line
Resoluiton	203 DPI(dot per inch)
Printing speed	90mm/s
Print width	48mm
Graphics printing	Supports bitmap download and print
Line Spacing	3.75 mm Can adjust line spacing by command
Line number	Font A:32 character /Line Font B:42 character/Line Simple,traditional Chinese-16 lines
Printing Command	Compatible with ESC/POS
Barcode	1D bar code UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128 2D bar code QR-CODE
Character	Standard GB18030 simplified / traditional Chinese Fonts
Character size	ANK character, Font A: 12*24dots, 1.5*3.0 mm Font B:9*17dots,1.1*2.1mm Simplified/Traditional Chinese: 24*24dots, 3.0*3.0mm

Character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858 IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257 Thai/Vietnam/PC864/PC1001/Latvian/PC1001/PT151,1251 WPC1257/PC864/Vietnam/Thai
<b>Media</b>	
Paper type	thermal roll paper
Paper width	57.5±0.5mm
Paper roll diameter	60mm Max
<b>Physical</b>	
dimension	185*130*112 mm
Weight	0.85kg
Package box	195*140*130 mm
24 in 1 carton	570*410*400mm/22kg
<b>Environment</b>	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation





THERMAL RECEIPT PRINTER

Model: OCPP-58E	Print Width: 58mm
Print Speed: 90mm/s	Power Input: 12V $\pm$ 3A
Cash Drawer: 12V $\pm$ 1A	Interface: USB
Print Commands: Support ESC/POS	



HTRP-58180400324

RoHS CE FC

















Model: 8000  
Capacity: 1000  
Interface: USB  
Loop Support: YES  
Print Density: Level-2  
Current Font: Font-A  
Support Character: Simplified Chinese (GB18030)  
Alphanumeric  
CODE BAR: 1. UPC-A 2. UPC-E



BT 3.0 & 4.0





