58mm Thermal Printer With Built-in Power Supply

(S/N: OCPP-58X)

Parameters:

Items		Parameters
Print parameters	Printing Method	Thermal Line
	Printing Width	48MM
	Resolution	384dots/Line(8dots/mm,203dpi)
	Printing Speed	90mm/Second
	Interface Type	USB,Parallel
	Line Spacing	3.75 mm(Can adjust line spacing by command)
	Line No.	Font A:32 character /Line Font B:42 character/Line Simple,traditional Chinese-16 lines
	Character	Standard GB2312 simplified Chinese Fonts
	Character Size	ANKcharacter,Font A:1.5×3.0mm(12×24dots) Font B:1.1×2.1mm(9×17dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots)
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/ EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/ PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257) /(PC864)/(Vietnam)/(Thai)
	Bar code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤60mm
	Feed Method	Easy feed(Clamshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input:AC 100V-240V,50-60Hz Output:DC 12V/2.6A
	Casher Drawer output	DC 12V/1A
Buffer	Input Buffer	32 KB
	NV Flash	64 KB

Aocom®
At your side
OCPP-58X
Aocom
At your side
ISO
FC
CE
RoHS

Ocom®

At your side

OCPP-58X

ISO FC CE RoHS

Aocom®
At your side
OCPP-58X
ISO
FC
CE
RoHS