OCPP-763C 76mm 24 pin impact ribbon dot matrix printer with auto cutter

Feature

76MM impact dot matrix receipt printer with automatic cutter; Compatible with EPSON; With Black mark detection function; Serial+USB interface; Support cash drawer kick out; Easy operation and elegant appearance.

Specification

Print font 9 pins serial dot matrix Column capacity 400dots Character size ANK, Font A:9*9dots, Font B:7*9dots Simplified Chinese, traditional Chinese:16*16dots Character set Buyer option Character per line 400dots Printing speed 4.5lines/sec Receive buffer Selectable as 45 bytes or 4k bytes using Dip switches Paper width 75.5±0.5mm Copy capability One original and two copies Ribbon ERC-39 MCBF(life) 10,000,000 lines Driver Win9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/Linux CPU 32 bit Storage environment Temperature (-10~60°c) humidity (10~90%) Working environment Temperature (0~50°c) humidity (10~90%) Dimension 230X146X145mm Gross weight 3.75KG Auto cutter Yes Paper end sensor Yes Paper end sensor Yes Paper end sensor 75.5±0.5mm* φ65mm Interface Serial+USB Command Compatible with EPSON	F=	
Column capacity400dotsCharacter sizeANK, Font A:9*9dots, Font B:7*9dots Simplified Chinese, traditional Chinese:16*16dotsCharacter setBuyer optionCharacter per line400dotsPrinting speed4.5lines/secReceive bufferSelectable as 45 bytes or 4k bytes using Dip switchesPaper width75.5±0.5mmCopy capabilityOne original and two copiesRibbonERC-39MCBF(life)10,000,000 linesDriverWin9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/LinuxCPU32 bitStorage environmentTemperature (-10~60°c) humidity (10~90%)Working environmentTemperature (0~50°c) humidity (10~90%)Dimension230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A	Printing method	9 pins serial dot matrix
Character size Character set Character set Character per line Printing speed Receive buffer Selectable as 45 bytes or 4k bytes using Dip switches Paper width Copy capability Ribbon Driver Win9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/Linux CPU 32 bit Storage environment Working environment Dimension Gross weight Dimension Gross weight ANK, Font A:9*9dots, Font B:7*9dots Simplified Chinese, traditional Chinese:16*16dots Buyer option 400dots 400dots 400dots 800dots 801dots 801dots 802lectable as 45 bytes or 4k bytes using Dip switches 9 selectable as 45 bytes or 4k bytes using Dip switches 9 selectable as 45 bytes or 4k bytes using Dip switches 9 selectable as 45 bytes or 4k bytes using Dip switches 9 selectable as 45 bytes or 4k bytes 6pondance 10 or 4conton 4conto		
traditional Chinese:16*16dots Character set Buyer option 400dots Printing speed A.5lines/sec Receive buffer Selectable as 45 bytes or 4k bytes using Dip switches Paper width 75.5±0.5mm Copy capability One original and two copies Ribbon ERC-39 MCBF (life) 10,000,000 lines Driver Win9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/Linux CPU 32 bit Storage environment Working environment Dimension 230X146X145mm Gross weight 3.75KG Auto cutter Yes Paper end sensor Paper thickness Roll paper 75.5±0.5mm* φ65mm Interface Serial+USB Command Compatible with EPSON Cash drawer control		100000
Character set Buyer option Character per line Printing speed 4.5lines/sec Receive buffer Selectable as 45 bytes or 4k bytes using Dip switches Paper width 75.5±0.5mm Copy capability One original and two copies Ribbon ERC-39 MCBF(life) 10,000,000 lines Driver Win9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/Linux CPU 32 bit Storage environment Working Temperature (-10~60°c) humidity (10~90%) environment Dimension 230X146X145mm Gross weight 3.75KG Auto cutter Yes Paper end sensor Yes Paper thickness 0.06-0.08mm Roll paper 75.5±0.5mm* φ65mm Interface Serial+USB Command Compatible with EPSON Cash drawer control	Character size	
Character per line Printing speed Receive buffer Selectable as 45 bytes or 4k bytes using Dip switches Paper width Copy capability One original and two copies Ribbon ERC-39 MCBF(life) Driver Win9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/Linux CPU 32 bit Storage environment Working environment Dimension 230X146X145mm Gross weight 3.75KG Auto cutter Paper end sensor Paper thickness Roll paper Interface Command Compatible with EPSON Cash drawer control A k bytes using Dip switches Selectable as 45 bytes or 4k bytes 6 6 6 6 7 6 7 6 7 6 7 6 7 6 7 6 7 6 7		traditional Chinese:16*16dots
Inine Printing speed 4.5lines/sec Selectable as 45 bytes or 4k bytes using Dip switches Paper width 75.5±0.5mm One original and two copies Ribbon ERC-39 MCBF(life) 10,000,000 lines Driver Win9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/Linux Temperature (-10~60°c) humidity (10~90%) Principal P	Character set	Buyer option
Printing speed 4.5lines/sec Receive buffer Selectable as 45 bytes or 4k bytes using Dip switches Paper width 75.5±0.5mm Copy capability One original and two copies Ribbon ERC-39 MCBF(life) 10,000,000 lines Driver Win9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/Linux CPU 32 bit Storage Temperature (-10~60°c) humidity (10~90%) environment Temperature (0~50°c) humidity (10~90%) Working Temperature (0~50°c) humidity (10~90%) Gross weight 3.75KG Auto cutter Yes Paper end sensor Yes Paper thickness 0.06-0.08mm Roll paper 75.5±0.5mm* φ65mm Interface Serial+USB Command Compatible with EPSON Cash drawer control DC 12-24V/1A	Character per	400dots
Receive bufferSelectable as 45 bytes or 4k bytes using Dip switchesPaper width75.5±0.5mmCopy capabilityOne original and two copiesRibbonERC-39MCBF(life)10,000,000 linesDriverWin9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/LinuxCPU32 bitStorage environmentTemperature (-10~60°c) humidity (10~90%)Working environmentTemperature (0~50°c) humidity (10~90%)Dimension230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A		
Ak bytes using Dip switches Paper width 75.5±0.5mm Copy capability One original and two copies Ribbon ERC-39 MCBF(life) 10,000,000 lines Driver Win9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/Linux CPU 32 bit Storage renvironment Working environment Dimension 230X146X145mm Gross weight 3.75KG Auto cutter Yes Paper end sensor Yes Paper thickness 0.06-0.08mm Roll paper 75.5±0.5mm* φ65mm Interface Serial+USB Command Compatible with EPSON Cash drawer control		·
Paper width75.5±0.5mmCopy capabilityOne original and two copiesRibbonERC-39MCBF(life)10,000,000 linesDriverWin9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/LinuxCPU32 bitStorage environmentTemperature (-10~60°c) humidity (10~90%)Working environmentTemperature (0~50°c) humidity (10~90%)Dimension230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A	Receive buffer	I
Copy capabilityOne original and two copiesRibbonERC-39MCBF(life)10,000,000 linesDriverWin9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/LinuxCPU32 bitStorage environmentTemperature (-10~60°c) humidity (10~90%)Working environmentTemperature (0~50°c) humidity (10~90%)Dimension230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A		
RibbonERC-39MCBF(life)10,000,000 linesDriverWin9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/LinuxCPU32 bitStorage environmentTemperature (-10~60°c) humidity (10~90%)Working environmentTemperature (0~50°c) humidity (10~90%)Dimension230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A		
MCBF(life)10,000,000 linesDriverWin9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/LinuxCPU32 bitStorage environmentTemperature (-10~60°c) humidity (10~90%)Working environmentTemperature (0~50°c) humidity (10~90%)Dimension230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A		·
DriverWin9X/Win ME/Win2000/Win2003/WinNT/Win XP/Win Vista/Win 7/LinuxCPU32 bitStorage environmentTemperature (-10~60°c) humidity (10~90%)Working environmentTemperature (0~50°c) humidity (10~90%)Dimension230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A	Ribbon	ERC-39
7/Linux CPU 32 bit Storage Temperature (-10~60°c) humidity (10~90%) environment Working environment Dimension 230X146X145mm Gross weight 3.75KG Auto cutter Yes Paper end sensor Yes Paper thickness 0.06-0.08mm Roll paper 75.5±0.5mm* φ65mm Interface Serial+USB Command Compatible with EPSON Cash drawer control	MCBF(life)	10,000,000 lines
CPU32 bitStorage environmentTemperature (-10~60°c) humidity (10~90%)Working environmentTemperature (0~50°c) humidity (10~90%)Dimension230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A	Driver	
Storage environmentTemperature (-10~60°c) humidity (10~90%)Working environmentTemperature (0~50°c) humidity (10~90%)Dimension230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A		•
environmentTemperature (0~50°c) humidity (10~90%)pimension230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A		
Working environmentTemperature (0~50°c) humidity (10~90%)Dimension230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A		Temperature (-10~60°c) humidity (10~90%)
environment230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A		
Dimension230X146X145mmGross weight3.75KGAuto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A		Temperature (0~50°c) humidity (10~90%)
Gross weight 3.75KG Auto cutter Yes Paper end sensor Yes Paper thickness 0.06-0.08mm Roll paper 75.5±0.5mm* φ65mm Interface Serial+USB Command Compatible with EPSON Cash drawer control		
Auto cutterYesPaper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A		
Paper end sensorYesPaper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A		
Paper thickness0.06-0.08mmRoll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A	Auto cutter	Yes
Roll paper75.5±0.5mm* φ65mmInterfaceSerial+USBCommandCompatible with EPSONCash drawer controlDC 12-24V/1A		
Interface Serial+USB Command Compatible with EPSON Cash drawer control DC 12-24V/1A		
Command Compatible with EPSON Cash drawer DC 12-24V/1A control		'
Cash drawer DC 12-24V/1A control	Interface	
control	Command	l '
	Cash drawer	DC 12-24V/1A
Power supply DC24V/2.5A	control	
	Power supply	DC24V/2.5A