

OCP-802 80mm Impact Thermal Printers for POS System (Model: OCP-802)

Specification:

Printing method	Direct thermal
Character size	ANK,FontA:12*24dots,FontB:9*17dots
Column capacity	576dots/line OR 512dots/line
Character set	PC347□Standard Europe□Katakana□ PC850□Multilingual□PC860□Portuguese□ PC863□Canadian-French□PC865□Nordic□ West Europe□Greek□Hebrew□East Europe□Iran□WPC1252□PC866□Cyrillic#2□ PC852□Latin2□PC858□IranII□Latvian□Arabic□PT151□1251□
Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39 /CODE93/CODE128
Printing speed	230mm/sec
Receive buffer	128k bytes
NV flash buffer	256K bytes
Paper width	79.5±0.5mm
MCBF(life)	100km
Printing command	Compatible with ESC/POS
Cash drawer control	DC 12-24V/1A
Paper thickness	0.06-0.08mm
Cutter	Manual Cutter
Roll paper	79.5±0.5mm* φ83mm
Interface	Serial/parallel/ USB/LAN
Driver	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/ Win Vista/win 7/Linux
Power supply	DC24V/2.5A
Power adapter input	AC 110V/220V, 50~60Hz ;output□DC 24V/2.5A
Dimension	190x145x150mm
Weight	3.5kg

Product Details:

