

80MM Thermal Receipt Printer with Auto Cutter

(Model: OCPP-80D)

Features:



Professional kitchen printer equipped with Flash LED light and big voice beeper, which remind the cook very well;

Support separate table receipt function;

Support continue mode;

Equipped with wall mounting, no need install hanging bracket manually;

100% Origin Japanese Mechanism, long lasting auto-cutter up to 1.5million cuts;

Variety interface can be option, serial+usb+lan, serial+usb+lan+wifi, serial+usb+lan+bluetooth;

Air printing can be option.

Specification

General		
Model	OCP-80DH	OCP-80DL
Optional Interface	URL/URLB/URLW for option	URL/URLB/URLW or UL for option
Input buffer	4MB	256KB
Printing Speed	300mm/S	300mm/S or 260mm/S
NV Flash	256KB	
Name	80mm desktop thermal printer with auto cutter	
Color	Black	
Power supply	Input: AC 100V-240V, 50-60Hz, Output: DC 24V/2.5A	
Cash drawer	DC 24V/1A	
Printer head lifespan	150KM	
Paper separator	48mm/52mm/56mm/64mm/68mm/76mm/80mm (optional)	
Cutter	Auto cutter	
Sensors	Paper out, cover open, cutter jam, paper jam and black mark detection(Optional)	
Accessories	Data cable, power adaptor, power cord, paper roller, CD, manual, Paper separator(optional)	
OS supporting	Compatible with iOS/ Android/ Windows/Linux	
Printing capability		
Printing method	Direct thermal line	
Resolution	203 DPI	
Print width	72mm	
Graphics printing	Supports bitmap download and print (each bitmap size Max.20K)	
Printing Command	Compatible with ESC/POS	
Barcode and character		
Bar-code	1D bar-code: UPC-A / UPC-E / JAN13/EAN13/ JAN8/EAN8/ CODE39 / ITF / CODABAR / CODE93 / CODE128 2D bar-codeQR CODE	
Fonts	ANK character: Font A: 12*24, Font B: 9*17 Chinese: GB18030, BIG5 24x24	
Japanese/Korea Optional	Support	
User-defined language	Support	

Media

Paper type	Thermal roll paper
Paper width	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Paper Thickness	0.06~0.08mm
Paper roll diameter	80mm Max
Paper separator	support

Physical

Dimension	186*143*140mm
Weight	1.0kg
Package box	228*215*165mm/1.9kg
8 in carton	476*446*348mm/15.5kg

Environment

Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation













