80mm thermal pos printer with Auto Cutter

Printing method:	Direct thermal
Printing speed:	230mm/s，260mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line，512 Dots/line
Line’s pacing :	3.75mm（Adjustable by commands）
Print command:	Compatible with the ESC/POS command
Interface type:	Serial+USB+Lan/36P parallel port/25P serial +USB/LAN
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V，50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0～45) humidity(10～80%)（Non- condense）
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10～60℃); Humidity(10～90%)
Character size:	ANK：FontA:1.5*3.0mm/ FontB：1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA：EAN13：/JAN8：EAN8/CODE39/ITF /CODE93/CODE128 QRCode
Characters:	PC347：Standard Europe，Katakana：PC850：Multilingual，PC860：Portuguese，PC863：Canadian-French，PC865：Nordic，West Europe：Greek：Hebrew：East Europe：Iran：WPC1252：PC866：Cyrillic#2，PC852：Latin2，PC858：IranII：Latvian：Arabic：PT151：1251：