

80MM Hight Speed Thermal Receipt Printer

(M/N:OCP-80F)



Feature:

- 1.300mm/s printing high-speed, improve the printing efficiency
- 2.2048K super input buffer, to avoid losing bills
- 3.Support 1D,2D bar code printing
4. Support black mark orientation and re-print
5. Support printer monitoring function, to avoid losing bills;
6. Excellent waterproof, anti - oil, anti-dust structure design
- 7.Movable baffle design, support 80MM,58MM different width of paper roll printing.

Printer Parameters:

Item	Parameters
Printing Method	Thermal Line
Printing width	72mm
Resolution	576 Dots/Line or 512 Dots/Line [8dots/mm,203dpi]
Print speed	300mm/Second
Interface	Internet [100M] +USB+COM;USB+COM
Line Spacing	3.75mm [Can adjust line spacing by command]
Line No.	FontA-48Lines/FontB-64Lines/Simple,traditional Chinese-24 lines
Character	standard GB18030 simplified / traditional Chinese Fonts
Character Size	ANK character, Font A:1.5×3.0mm [12×24 dots] FontB:1.1×2.1mm [9×17 dots] [Simplified/Traditional Chinese:3.0×3.0mm (24×24 dots)]
Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/ EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/ PC737/WPC/1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)

Bar code	1D barcode:UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128
	2D barcode[]QRCODE
Graphics printing	Supports bitmap download and print
Cutter Function	Half cut
Type	Thermal
Width	79.5±0.5mm
Diameter	≤80mm
Feed method	Easy feed(Clameshell feed)
Commands	ESC/POS
Power Adaptor	Input:AC 110V/220V,50~60Hz
	Output:DC 24V/2.5A
Cash Drawer output	DC 24V/1A
Input Buffer	2048K bytes