

OCPP-80E USB / parallel auto cutter 80mm cheap receipt printer pos thermal

Printing method:	Direct thermal
Printing speed:	230mm/s□260mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line□512 Dots/line
Line's pacing :	3.75mm□Adjustable by commands□
Print command:	Compatible with the ESC/POS command
Interface type:	Serial+USB+Lan/36P parallel port/25P serial +USB/LAN
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V□50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0□45) humidity(10□80%)□Non- condense□
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10□60°C); Humidity(10□90%)
Character size:	ANK□FontA:1.5*3.0mm/ FontB□1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA□EAN13□JAN8□EAN8/CODE39/ITF /CODE93/CODE128 QRCode
Characters:	PC347□Standard Europe□Katakana□PC850□Multilingual□PC860□Portuguese□PC863□Canadian-French□PC865□Nordic□West Europe□Greek□Hebrew□East Europe□Iran□WPC1252□PC866 □Cyrillic#2□PC852□Latin2□PC858□IranII□Latvian□Arabic□PT151□1251□



Relevant documents:

[*Specification](#)

[*IP Address Configure Manual](#)

[*Instruction Manual](#)

[*Driver for all windows system](#)

[*Driver for Linux](#)

[*Printer Parameters Setting Tools](#)

[*CD Files](#)