

# OCPP-80F:80mm or 58mm usb mobile thermal pos receipt printer

(M/N:OCPP-80F)

## Feature:

- 1.300mm/s printing high-speed, improve the printing efficiency
- 2.2048K super input buffer, to avoid losing bills
- 3.Support 1D,2D bar code printing
4. Support black mark orientation and re-print
5. Support printer monitoring function, to avoid losing bills;
6. Excellent waterproof, anti - oil, anti-dust structure design
- 7.Movable baffle design, support 80MM,58MM different width of paper roll printing.

## Printer Parameters:

Item	Parameters
Printing Method	Thermal Line
Printing width	72mm
Resolution	576 Dots/Line or 512 Dots/Line@8dots/mm,203dpi
Print speed	300mm/Second
Interface	Internet(100M)+USB+COM+USB+COM
Line Spacing	3.75mm(Can adjust line spacing by command)
Line No.	FontA-48Lines/FontB-64Lines/Simple,traditional Chinese-24 lines
Character	standard GB18030 simplified / traditional Chinese Fonts
Character Size	ANK character,Font A:1.5x3.0mm(12x24 dots) FontB:1.1x2.1mm(9x17 dots)(Simplified/Traditional Chinese:3.0x3.0mm(24x24 dots))
Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/rani/Latvian/Arabic/PT151,1251/PC737/WPC1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Bar code	1D barcode:UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128 2D barcode:QR CODE
Graphics printing	Supports bitmap download and print
Cutter function	Half cut
Type	Thermal
Width	79.5±0.5mm
Diameter	≤80mm
Feed method	Easy feed(Clameshell feed)
Commands	ESC/POS
Power Adaptor	Input:AC 110V/220V,50-60Hz Output:DC 24V/2.5A
Cash Drawer output	DC 24V/1A
Input Buffer	2048K bytes
NV Flash	256K bytes
Weight	1.2KG
Dimension	186*145*135
Working	Temp:-5~45 Centigrade, Humidity:10~80%
Storage	Temp:-10~50 Centigrade, Humidity:10~90%(Nodew)
Print Head Life	10000(print density LE12.5)
Cutter Life	1000,000times
Driver	Android,IOS, Linux, Win2000, Win2003, WinXP, Win7, Win8, Win8.1