80mm thermal receipt printer support Bluetooth and WIFI

(Model: OCPP-80F)

Feature:

- 1.300mm/sprintinghigh-speed, improve the printing efficiency
- 2.2048Ksuper input buffer, to avoid losing bills
- 3.Support1D,2D bar code printing
- 4. Support black markorientation and re-print
- 5. Support printer monitoringfunction, to avoid losing bills;
- 6.Excellent waterproof, anti oil, anti-dust structure design
- 7.Movablebaffle design, support 80MM, 58MM different width of paperroll printing.

Printer Parameters:

Item	Parameters
Printing Method	Thermal Line
Printing width	72mm
Resolution	576 Dots/Line or 512 Dots/Line[Bdots/mm,203dpi[]
Print speed	300mm/Second
Interface	Internet[]100M[]+USB+COM;USB+COM
Line Spacing	3.75mm[Can adjust line spacing by command[]
Line No.	FontA-49Lines/FontB-64Lines/Simple,traditional Chinese-24 lines
Character	standard GB18030 simplified / traditional Chinese Fonts
Character Size	ANK character, Font A:1.5×3.0mm[]12×24 dots[]
	FontB:1.1x2.1mm[9x17 dots] Simplified/Traditional Chinese:3.0x3.0mm(24x24 dots]
Extended character set	PC437/Katakana/PC850/PC863/PC865/PC865/PC865/PC865/PC965/PC965/PC965/PC965/PC965/PC965/PC965/PC965/PC852/PC858/PC858/PC858/PC858/PC858/PC858/PC854/PC852/PC858/PC854/PC8
Bar code	ID barcode-UPC-AUPC-EJAN13(EAN13)/JAN8(EAN13)/JAN8(EAN18)CODE39/ITF/ CODABAR/CODE39/CODE128
	2D barcode[QRCODE
Graphics printing	Supports bitmap download and print
Cutter Function	Half cut
Туре	Thermal
Width	79.5±0.5mm
Diameter	≤80mm
Feed method	Easy feed(Clameshell feed)
Commands	ESC/POS
Power Adaptor	Input:AC 110V/220V,50~60Hz
	Output:DC 24V/2.5A
Cash Drawer output	DC 24V/IA
Input Buffer	2048K bytes
NV Flash	256K bytes
Weight	1.2KG
Dimension	186*145*135
Working	Temp:5~45 Centigrade,Humidity:10~80%
Storage	Temp::10 ~ 50 Centigrade, Humidity:10~90%(Nodew)
Print Head Life	100KM(print density LE.12.5)
Cutter Life	1000,000times
Driver	Android,IOS,Linux,Win2000,Win2003,WinXP,Win7,Win8,Win8.1



Relevant documents:

Driver and CD files