

cheap 3 inch pos bluetooth thermal receipt printer for Andriod or IOS

(M/N:OCPP-80F)

Feature:

- 1.300mm/sprintinghigh-speed, improve the printing efficiency
- 2.2048Ksuper input buffer,to avoid losing bills
- 3.Support1D,2D bar code printing
- 4. Support black markorientation and re-print
- 5. Support printer monitoringfunction,to avoid losing bills;
- 6.Excellent waterproof, anti - oil, anti-dust structure design
- 7.Movablebaffle design,support 80MM,58MM different width of paperroll printing.

Printer Parameters:

| | |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item | Parameters |
| Printing Method | Thermal Line |
| Printing width | 72mm |
| Resolution | 576 Dots/Line or 512 Dots/Line[8dots/mm,203dpi] |
| Print speed | 300mm/Second |
| Interface | Interne[100M]+USB+COM;USB+COM |
| Line Spacing | 3.75mm[Can adjust line spacing by command] |
| Line No. | FontA-48Lines;FontB-64Lines;Simple,traditional Chinese-24 lines |
| Character | standard GB18030 simplified / traditional Chinese Fonts |
| Character Size | ANK character,Font A:1.5x3.0mm[12x24 dots] FontB:1.1x2.1mm[9x17 dots][Simplified/Traditional Chinese:3.0x3.0mm[24x24 dots] |
| Extended character set | PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/Thai/Vietnam/PC864/PC1001/Latvian/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai) |
| Bar code | 1D barcode:UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128 2D barcode:QRCODE |
| Graphics printing | Supports bitmap download and print |
| Cutter Function | Half cut |
| Type | Thermal |
| Width | 79.5±0.5mm |
| Diameter | ≤60mm |
| Feed method | Easy feed(Clameshell feed) |
| Commands | ESC/POS |
| Power Adaptor | Input:AC 110V/220V,50~60Hz Output:DC 24V/2.5A |
| Cash Drawer output | DC 24V/1A |
| Input Buffer | 2048K bytes |
| NV Flash | 256K bytes |
| Weight | 1.2KG |
| Dimension | 186*145*135 |
| Working | Temp:-5~45 Centigrade,Humidity:10~80% |
| Storage | Temp:-10 ~ 50 Centigrade,Humidity:10~90%(Nodew) |
| Print Head Life | 100KM(print density LE12.5) |
| Cutter Life | 1000,000times |
| Driver | Android,IOS,Linux,Win2000,Win2003,WinXP,Win7,Win8,Win8.1 |