

# 80MM Thermal Printer with Auto Cutter

(Model No.: OCPP-80H)

## I Features:

- I Desktop or wall-mounted type for option.
- I Supports multi 1D barcodes and 2D codes printing.
- I USB+RS232+LAN,3 interface
- I 300mm /S high printing Speed
- I 100M Ethernet port ultra high speed data transmission.
- I Supports 256KB NV Logo storage and 2M big buffer memory.
- I Supports black mark detection and order reminding function,
- I Compatible with OPOS driver.

## Technical parameters:

Printing method:	Direct thermal
Printing speed:	300mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line512 Dots/line
Line's pacing :	3.75mm(Adjustable by commands)
Print command:	Compatible with the ESC/POS command
Interface type:	Serial+USB+LAN
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V,50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0~45) humidity(10~80%)(Non- condense)
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10~60°C); Humidity(10~90%)
Character size:	ANK,FontA:1.5*3.0mm/ FontB:1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8/CODE39/ITF /CODE93/CODE128/QRCode/PDF417 (options)
Characters:	PC347(Standard Europe),Katakana,PC850(Multilingual),PC860(Portuguese),PC863(Canadian-French),PC865(Nordic),West Europe,Greek,Hebrew,East Europe,Iran,WPC1252,PC866(Cyrillic#2),PC852(Latin2), PC858,IranII,Latvian,Arabic,PT151(1251)



# OCPP-80H



**Attention:** Press FEED or re-start to reset cutter when it or cover stuck. If not, open here and turn the gear to reset cutter





# OCPP-80H





OCPP-80H





OCPP-80H





OCPP-80H

