

(OCPP-80K) Thermal Receipt Printer With Auto Cutter Mobile 58mm 80mm Wifi Bluetooth

(M/N:OCPP-80K)



Features:

It can be used as top paper coming printer and front paper coming printer

It's built-in power adaptor, which avoids messy cords everywhere, saving much space

Support 8 kinds abundant interface combination

Supports multi 1D barcode and QR code printing

Support printer status monitoring function

Support printing queuing ticket function

100M Ethernet port, ultra high speed data transmission

256KB NV Logo storage and 256kb big buffer memory

48 or 80mm adjustable paper separator for option

100KM long life printer head

Specifications:

General	
Model	DCP-80K
Name	80mm desktop thermal printer with auto cutter
Color	Black
Interface	USB/USB+LAN/USB+BT/USB+WIFI/URL+WIFI/URL+BT/USB+RS232
Power supply	Input:AC 100V-240V/50-60Hz,Output:DC 24V/2.5A
Cash drawer	DC 24V/1A
Graphics printing	Supports bitmap download and print (each bitmap size Max 20K)
Printer head lifespan	100KM
Cutter	Auto cutter
Sensors	Paper out, cover open, cutter jam,paper jam and black mark detection(Optional)
Buffer	Print buffer:256K/UV Flash 256K
Accessories	Data cable,power adaptor,power cord,paper roller,CD,manual, Paper separator(optional)
OS supporting	Compatible with IOS/ Android/ Windows
Safety standards	CE ,FCC,Rohs etc.
Printing capability	
Printing method	Direct thermal line
Resolution	378 Dots/Line or 512 Dots/Line(8dots/mm, 203dpi)
Printing speed	200mm/s (USB) 260mm/s (URL+BT/ U+ WIFI) 200mm/s (URL/ URL+BT/ URL+WIFI)
Print width	72mm
Graphics printing	Supports bitmap download and print
Printing Command	Compatible with ESC/POS
Barcode and character	
Barcode	1D barcode: JPC-A/JPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/ITF/COUPON/CODE93/CODE128 2D barcode:QR_CODE/Single USB or UR solution no QR code function
Character	Standard GB18030 simplified / traditional Chinese Fonts
Character size	384dots/line, AWK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm FontB:9*17dots, 1.1(W)*2.1(H)mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Japanese/Korea	Optional
User-defined language	PC437/Katakana(PC850/PC860/PC863/PC865/WesteEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/Iran/Latvian/Arabic/PT151.1251/PC737/WPC1257/Thai/Vietnam/PC864/PC1001/Latvian/PC1001/PT151.1251/WPC1257/PC864/Vietnam/IThai)
Media	
Paper type	Thermal roll paper
Paper width	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Paper Thickness	0.08-0.09mm
Paper roll diameter	83mm Max
Paper separator	Optional
Physical	
Dimension	198*145*135mm
Weight	1.65kg
Package box	300*190*180 mm
12 in 1 carton	615*370*335mm/21.5kg
Environment	
Working temperature& humidity	0 to 45 degrees centigrade, 10%–80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade, 10%–90% No condensation

Product details:

