

80MM Front Feed Paper POS Thermal Receipt Printer

(Model No.: OCPP-80M)

Features:

260mm/sec High Speed Printing;
Auto Cutter Life: 1 million cuts;
Support QR CODE Printing;
Serial + USB + LAN Interfaces;
Support International Language;
Printer Status Monitoring;
Support sound and light reminder function;
Front paper design prevents water splashing;
Suitable for kitchen applications.

Specification:

| | |
|----------------------------|--|
| Printing Method | Direct Thermal |
| Character Size | ANK,FontA:12*24dots,FontB:9*17dots,Simplified/Traditional Chinese :24*24 dots |
| Column Capacity: | 576dots/line OR 512dots/line |
| Code Page | PC347(Standard Europe),Katakana, PC850(Multilingual),PC860(Portuguese), PC863(Canadian-French),PC865(Nordic), West Europe,Greek,Hebrew,East Europe,Iran,WPC1252,PC866(Cyrillic#2),PC852(Latin2), PC858(Latin2),IranII,Latvian,Arabic,PT151(1251) |
| Barcode | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/ CODE128 |
| Printing Speed | 260mm/sec |
| Input Buffer | 1024K bytes |
| Paper Width | 79.5±0.5mm |
| MCBF(life) | 100km |
| Printing Command | Compatible with ESC/POS |
| Cash Drawer Control | DC24V/1A |
| Paper Thickness | 0.06-0.08mm |
| Cutter | Manual Cutter |
| Roll Paper | 79.5±0.5mm* φ83mm |
| Interface | Serial + USB + LAN |
| Drivers | Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/win 7&8/Linux/win10 |
| Power Supply | DC24V/2.5A |
| Power Adapter Input | AC 110V/220V, 50~60Hz ;output:DC 24V/2.5A |
| Dimension | 185x140x134mm(L*W*H) |
| Weight | 1.48kg |



OCPP-80M





OCPP-80M





OCPP-80M





Relevant documents:

[OCP-80M SPEC](#)